

# LOCK'ER<sup>®</sup> DOWN



LD6030 Install Video

## SECURITY PRODUCTS INSTALLATION INSTRUCTIONS

**LD6030/LD6030EX**

[ 2020-2022 Kia Telluride ]

1. For any combination style lock, it is a good idea to set the combination before installing the safe. We recommend that the combination be set with the **DOOR OPEN** in order to test the lock combination effectively without locking yourself out.
2. Clear out the contents of the center console for now, including the factory mat at the bottom of the console.
3. Remove the **2** bolts at the bottom of the console (these can be discarded as they are no longer needed).
4. Remove the padding from the bottom of the inside of the safe.
5. Set the safe into the center console.
  - a. To ensure that the safe is sitting in the console correctly, make sure that the slots at the bottom of the safe line up with the factory bolt holes in the console compartment.
6. Using your 10mm fastening device, insert the **LOCK'ER DOWN PROVIDED 10MM BOLTS** into the factory holes at the bottom of the safe (these holes should line up with the factory screw holes at the bottom of the compartment)
7. Tighten the bolts, **DO NOT OVER TIGHTEN, THIS COULD DAMAGE THE CONSOLE.**
8. Re-insert the padding that was removed from the safe before installation.
9. Enjoy your purchase!

### Tools Needed:

- **IMPACT DRILL** or **SOCKET WRENCH**
- 10mm Socket bit

**Contents Included:** **2** 10mm Bolts.

