

MDS-6EXTF



Low-Mid Rise Lifts

SKU# 5175151

6,000-lb. Capacity / Mid-Rise Lift / Extended Platform / Open Center / Flush-Mount

Questions? Contact BendPak's Sales Team

sales@bendpak.com | 1-800-253-2363

Monday - Friday, 7AM to 4:30PM PST

Install an Extended Mid-Rise Lift Flush Over Work Pits

The MDS-6EXTF extended-length, flush-mount, [mid-rise lift](#) is the ideal solution for quick-lube stations looking to install a car lift flush over their work pits. If your shop wants to be ready for longer-wheelbase vehicles and minimize the lift's footprint, you can't do better than the BendPak MDS-6EXTF.



Features

- 6,000-lb. lifting capacity
- Open-center design / flush-mount
- Adjustable arm assemblies
- Solid-steel safety lock bars
- Multiple lock positions
- Hinge-point with Zerk grease fittings
- Low-profile design
- Rubber blocks included
- Removable ramps

Specifications

Lifting Capacity	6,000 lbs. (2,724 kg)
Lift Height w/o Blocks	32.3" (820 mm) Flush-Mounted
Lift Height + Blocks	33.8" (858.5 mm) Flush-Mounted
Lift Platform Dimensions	19" x 78.7" (484 mm x 2,000 mm)
Width Between Platforms	40" to 46" (1,018 mm to 1,168 mm)
Overall Width	19" (484 mm)
Overall Length	78.7" (2,000 mm)
Lowered Height	Flush with ground
Lifting Time	35 sec
Motor (*)	110-220 VAC / 60 Hz / 1 Ph

* Special voltage available on request.

Design, materials, and specifications shown here are subject to change without notice.

Note: An air supply (minimum 50 psi / 10 CFM) is required for the safety-lock mechanisms to disengage. It is solely your responsibility to install and maintain the air supply.

Not all BendPak lift models meet the standards as prescribed by ANSI/ALI ALCTV-2017 or ANSI/UL 201. Consult www.autolift.org for complete listings or contact BendPak via contact@bendpak.com.