

ADVANCED PHOTONICS UNIVERSAL MULTI-VOLTAGE GROUND FORCE BATTERY PACK MVP-240

The MVP-240 is the only battery pack on the market capable of supplying three different voltages to provide reliable and uninterrupted power to a wide variety of electronic and electro-optical systems. It is a universal powering tool for lengthy missions in remote locations where battery charging equipment is not accessible.

The MVP-240 is particularly useful with helmet-mountable NVGs. Instead of carrying "dead weight" in a form of a standard counterweight at the back of a helmet, the MVP-240 serves a dual purpose by supplying power to the NVG while being a counterweight at the same time.



MAIN CHARACTERISTICS:



The MVP-240 can be mounted on a firearm's Picatinny rail to substantially increase operation time of a night vision, thermal, or fusion rifle scope without obstructing access to main controls of a firearm. The excellent weight distribution of this battery pack makes operation of a firearm just as comfortable as if the MVP-240 was not attached at all.

For the user's convenience and freedom of choice, the MVP-240 does not have or use any proprietary or built-in batteries. It accepts all standard AA batteries widely available anywhere in the world: Alkaline, Ni-MH / Rechargeable, Lithium, and so on.

KEY FEATURES:

12V Port 3V Port > Adds up to 240 Hours to NVG Operation Time Left/Off/Right Chamber 5V Port > Tri-Port Design: Supplies 3VDC, 5VDC, and 12VDC Selector Switch > Weighs and Feels as Standard NVG Counterweight Waterproof Enclosure > Accepts 8 Standard AA Batteries of Any Kind Lever for Quick > Fits Firearms' Rails and Helmets Attach Mount > Compact Dual-Chamber Enclosure > Mil-Spec Compliant Each Chamber Holds > Convenient Power Selector 4 AA Batteries > Comes with Slide-and-Lock Picatinny Rail Inserted into "Quick > In-Built MIL-STD-1913 Mount w/Quick Release Lever Swap" Battery > Powers Night Vision / Thermal / Fusion and Other Cartridges. Electronic / Electro-Optical Systems YEARS YEARS Designed, Developed, Manufactured by GSCI Advanced Photonics 120 WHITMORE ROAD, UNIT 20, WOODBRIDGE, ONTARIO, L4L6A5, CANADA WWW.GSCI.NET | GSCI@GSCI.NET | +1.905.850.0990





UNIVERSAL MULTI-VOLTAGE GROUND FORCE BATTERY PACK

MVP-240



MVP-240 can be attached to the back of the helmet by using Velcro® or enclosed Picatinny rail



The add-on Slide-and-Lock Picatinny Rail allows attaching the MVP-240 to virtually any surface



MVP-240 can be attached to any optical-electronic device which already has service Picatinny rail or by using enclosed Picatinny rail

TECHNICAL SPECIFICATIONS	
Compatibility with GSCI Devices	All GSCI-Made Devices with External Power Port
Compatibility with Other Devices	All Electronic / Electro-Optical Devices that Accept 3VDC, 5VDC or 12VDC External Power Input and Electronic Devices that Accept USB Power Input: Cell Phones, Tablets, etc.
Accepted Batteries	8pcs AA of Any Kind: Lithium, Rechargeable (Ni-MH), Alkaline, etc.
Attachment to Helmet	Velcro [®] or Quick Release Picatinny Mount via Slide-and-Lock Rail
Attachment to Firearm	Quick Release Picatinny Mount
Maximum Operation Time: NVG ¹	240 Hours
Maximum Operation Time: Thermal Device ²	25 Hours
Maximum Operation Time: Fusion Device ³	15 Hours
Body Material	Hard Anodized Aluminum
Dimensions	93x48x115 mm 3.66 x 1.89 x 4.53 in
Weight without Batteries*	330 grams 0.72 lbs
MIL-STD-810 Compliance	Yes
MIL-STD-461 Compliance	Yes
Warranty	7 Years
Export	Available Worldwide: No Export License Required

Maximum operation times are given for GSCI-made devices when the MVP-240 is equipped with 8pcs brand new lithium batteries:

¹ - Dual-Tube Night Vision Goggles PVS-31C-MOD

² - Thermal Imaging Device TI-GEAR Series

³ - Fusion Device QUADRO-S

CLAIMER. Technical description, certain optical-electronic-mechanical features of the product shown herein and/or some of its parts/comp ige without prior notice by the sole discretion of General Starlight Co., Inc., Mass of the product represents measurable weight of all itornics. Dimensions of the product represents measurable size of the body, including all optical components attached and in fully folded ctive lens covers, and/or battery extensions may vary and therefore are not listed herein. Copyright © 1992-2023 General Starlight Co., Inc.

Maximum operation times on other systems may vary.

*Actual weight of the MVP-240 with batteries varies depending on a battery type being used.

new not precisely represent the actual device and are subject to ents this product consists of, such as optics, mechanics, and Dimensions of additions such as mounting brackets, eyecups, All rights reserved.

Kit Contents (What's in the Box): MVP-240 Battery Pack, Picatinny Rail, Power-Out Cable, 4 pcs. of "Quick Swap" Battery Cartridges, Soft Carrying Pouch. *Note: Batteries are not included.*