



# PRECISION THERMAL CLIP-ON SCOPE

### TI-GEAR-C345

The TI-GEAR-C345 is the professional-grade thermal clip-on sight for aiming and engagement designed to work seamlessly with a wide variety of firearms and daytime scopes. The TI-GEAR-C345 is a plug-and-play unit, deployed in mere seconds with no zeroing needed. It is also a great tool for reconnaissance and tactical surveillance.

The latest generation silent and Auto-NUC sensor is at the base of the TI-GEAR-C345. GSCI proprietary hardware and software solutions are built around the sensor and offer exceptional image quality along with unique tools for added tactical advantage and user safety.

The TI-GEAR-C345 is fully dust- and waterproof, meets and exceeds modern standards. The TI-GEAR-C345 is designed for both professional users and also firearms enthusiasts. It is a robust, reliable tool for long-term, intensive use in any environment, in any lighting or weather conditions.

#### **ADVANTAGES OF TI-GEAR-C345**



Designed, Developed, Manufactured by GSCI Advanced Photonics
120 WHITMORE ROAD, UNIT 20, WOODBRIDGE, ONTARIO, L4L6A5, CANADA
WWW.GSCI.NET | GSCI@GSCI.NET | +1.905.850.0990

DISCLAIMER. Fechnical description, certain optical-electronic-mechanical rearrures of the product shown nerein and/or some of its parts/components may not precisely represent me actual device and are subject to change without prior notice by the sole discretion of General Starlight Co., Inc. Mass of the product represents measurable every components this product consists of, such as optics, mechanics, and electronics. Dimensions of the product represents measurable size of the body, including all optical components attached and in fully folded position. Dimensions of additions such as mounting brackets, eyecups, objective lens covers, and/or battery extensions may vary and therefore are not fisted herein. Copyright © 1992-2023 General Starlight Co., Inc. Change. All rights reserved.





# PRECISION THERMAL CLIP-ON SCOPE

## TI-GEAR-C345

#### Every TI-GEAR-C345 Clip-On Sight can be used in 3 main configurations



Clip-On (In-Line) Sight

On-Rail or On-Scope Configuration



Standalone Sight

Direct View Eyepiece and Weapon Mount are Required



Hand-Held

Direct View Eyepiece is Required, Removing Weapon Mount (if equipped) is not necessary





#### ADVANCED PHOTONICS

## PRECISION THERMAL CLIP-ON SCOPE

### TI-GEAR-C345

	Optical Magnification	1X
	Objective Lens System	45mm
	Field of View	8.3°x6.2°
	Focusing Range	1.5m Infinity
	FPA Type	Uncooled, a-Si, Shutterless, Silent, Auto-NUC (Uninterrupted Operation)
	FPA Resolution and Pitch	384x288, 17µm
	FPA Sensitivity (NETD)	<40mK
	FPA Refresh Rate	50Hz
	Digital Zoom	1X, 2X, 4X
	Internal Display	Full Size: 0.6-Inch Diagonal, AMOLED, Colour, 800x600
	Imaging Modes	Monochrome (White-Hot / Black-Hot) and 8 Colour Palettes
	Shot-Initiated FOV Feature (SIF)	Built-In Adjustable Shock Sensor
	Digital Passive Stadiametric Rangefinder (SRF)	Yes
-G	Digital Detail Enhancement Feature (DDE)	Yes
П	Wide Dynamic Range Feature (WDR)	Yes
AR-	Stow Safety Feature (SSF)	Yes
?-C	Integrated 9-Axis Absolute Orientation HUD (Heads-Up Display)	Optional: 3-Axis Sensors - Magnetometer, Accelerometer and Gyroscope
သ	Integrated Compass	Optional
45	Pitch / Roll / Azimuth Indications	Optional
$\dashv$	Real-Time Date-Time Stamp	Yes: Simplified, Extended, DTG Formats
EC	Digital Video Recorder with Real-Time Stamp	Optional: Comes with removable 32GB microSD card
СН	Electronic Reticles	Can be Enabled for Standalone Sight Configuration: 8+8 Patterns, Easy Zeroing / Calibration
NIC	Detection Capability: Man (1.7x0.5m) / NATO Target (2.3x2.3m)	1500m / 2030m
C	Mounting to Dayscope	On-Rail, On-Scope Direct, On-Scope Via Clamp/Adapter
$\triangleright$	Optimal Dayscope Magnification Range	3X 12X
	Hand-Held / Tripod-Mounted Capability	Yes: Hand-Held and Tripod-Mountable
DΑ	Conversion to Standalone (Direct View) Sight	Yes
AT.	User Profiles (Configurable)	Yes: 8
$\triangleright$	Automatic/Manual Pixel Masking	Yes
	Reset to Factory Defaults	Yes
	External Video Feed Protection	Yes
	Automatic Power Down Control	User-Configurable: 10 60 minutes of inactivity
	Accepted Batteries	2 (two) CR123 of Any Type: Lithium / Rechargeable
	Universal Port	Video-Out, Remote Control and External Power (4VDC 15VDC)
	Battery Life on 2x CR123	Up to 7 Hours
	Environmental Protection	Min. IP67, Nitrogen-Purged Housing
	Dimensions	183 x 60 x 60 mm
	Weight	545 grams
	Operating Temperature	-40°C +50°C
	Warranty	7 Years, Limited
	Made In Canada	ITAR-Free





# PRECISION THERMAL CLIP-ON SCOPE

### TI-GEAR-C345

STANDARD EQUIPMENT: WHAT'S IN THE BOX		
1	Thermal Imaging Clip-On Sight	
2	Clip-On Eyepiece with Rubber Shroud (Attached)	
3	Front Lens Protective Cover (Attached)	
4	Dual Lever Adjustable Rifle Mount DLM (Picatinny, with fine-tune knobs for tolerance adjustments)	
5	USB Power Cable	
6	Video-Out Cable	
7	Soft Carrying Pouch	
8	User Manual	
9	Quick Reference Card	
10	7-Year Warranty with Activation Form	
11	Waterproof Hard Carrying Case	
12	Cleaning Kit (3-in-1 Multi-Pen + Cleaning Cloth)	

<sup>\*</sup> Batteries not included

	OPTIONAL EQUIPMENT
Α	Universal Remote Control Unit TRC-120 (Comes with connection cable)
В	Universal Multi-Voltage Battery Pack MVP-240 (Comes with connection cable)
С	Built-In Digital Video Recorder <b>GS-DVR-INT</b> (Comes with 32GB microSD card and SD adapter)
D	External Digital Video Recorder GS-EDVR (Comes with set of cables and 32GB SD card)
Е	Portable Head-Mounted Display HMD-800-MOD (streams thermal video directly from the device)
F	MTAR™-HUD Heads Up Display (streams video directly from the unit; equipped with built-in DVR, GPS and Integrated 9-Axis Absolute Orientation HUD )
G	Integrated <b>9-Axis Absolute Orientation HUD</b> (Heads-Up Display), 3-Axis Sensors for Compass Reading, Inclinometer/Pitch Reading, and Level/Roll Reading
Н	Heavy-Duty Quick Release Rifle Mount MAK-QR-BLASER (Blaser, Adapter included)
I	Heavy-Duty Quick Release Rifle Mount MAK-QR-PICATINNY (Picatinny, Adapter included)
J	Heavy-Duty Rifle Mount MAK-PICATINNY (Picatinny, Adapter included, Allen Key Included)
K	Adapter for MAK Mount: Regular Length (ADAPTER-REG) or Extended Length (ADAPTER-EXT)
L	Direct View Eyepiece GSCI-LR-EYEPIECE
М	Day Scope Adapter Clamp for COA for direct mounting onto daytime optics, CO-DSA (various sizes available)
N	Long Eyerelief Rubber Eyecup GSCI-EYECUP-LR