



ADVANCED PHOTONICS PRECISION THERMAL RIFLE SCOPE

TI-GEAR-S650F

The TI-GEAR-S650F is the professional-grade thermal weapon sight for aiming and engagement on a wide variety of firearms at mediumrange distances. Ideal for both small, large-size caliber rifles, machine guns, whether single or repetitive shooting. It is also a great tool for reconnaissance and tactical surveillance.

The latest generation silent and Auto-NUC sensor is at the base of the TI-GEAR-S650F. GSCI proprietary hardware and software solutions are built around the sensor and offer exceptional image quality along with unique tools for added tactical advantage and user safety.

The TI-GEAR-S650F is fully dust- and waterproof, meets and exceeds modern standards. The TI-GEAR-S650F is designed for both professional users and also firearms enthusiasts. It is a robust, reliable tool for long-term, intensive use in any environment, in any lighting or weather conditions.

ADVANTAGES OF TI-GEAR-S650F

Comfortable Eyepiece

with Long Eyerelief

Full-Size Colour **AMOLED Display**

All-Aluminum Rugged Housing

High-Performance, Auto-NUC, Shutterless, Silent FPA

Canadian-Made, ITAR-Free System

Ergonomic Keypad, User-Friendly Interface



Multi-Use Picatinny Side Mounting Bracket

> Smooth and Precise Focus Adjustment

> > Fast Germanium Objective Lens

Variety of Rifle Mounts Available









Designed, Developed, Manufactured by GSCI Advanced Photonics
120 WHITMORE ROAD, UNIT 20, WOODBRIDGE, ONTARIO, L4L6A5, CANADA
WWW.GSCI.NET | GSCI@GSCI.NET | +1.905.850.0990





TI-GEAR-S650F

Every TI-GEAR-S650F Sight can be used in 3 main configurations



Hand-Held

Removing Weapon Mount is not necessary



Standalone Sight



Clip-On (In-Line) Sight

Clip-On Adapter Required, Scope Adapter Optional (Configuration-Dependent)





PRECISION THERMAL RIFLE SCOPE TI-GEAR-S650F

| Optical Magnification | | 2X |
|--|------------------------|---|
| Objective Lens System | | 50mm |
| Field of View | | 12.4°x9.3° |
| Focusing Range | | 1.5m Infinity |
| Diopter Adjustment Range | | -6 +4 |
| Eyerelief | | Min. 50mm |
| FPA Type | | Uncooled, a-Si, Shutterless, Silent, Auto-NUC (Uninterrupted Operation) |
| FPA Resolution and Pitch | | 640x480, 17μm |
| FPA Sensitivity (NETD) | | <40mK |
| FPA Refresh Rate | | 50Hz |
| Digital Zoom | | 1X, 2X, 4X, 8X |
| Internal Display | | Full Size: 0.6-Inch Diagonal, AMOLED, Colour, 800x600 |
| Imaging Modes | | Monochrome (White-Hot / Black-Hot) and Multiple Colour Palettes |
| Shot-Initiated FOV Feature (SIF) | | Built-In Adjustable Shock Sensor |
| Digital Passive Stadiametric Rangefind | ler (SRF) | Yes |
| Digital Detail Enhancement Feature (DI | DE) | Yes |
| Wide Dynamic Range Feature (WDR) | | Yes |
| Stow Safety Feature (SSF) | | Yes |
| Integrated 9-Axis Absolute Orientation | HUD (Heads-Up Display) | Optional: 3-Axis Sensors - Magnetometer, Accelerometer and Gyroscope |
| Integrated Compass | | Optional |
| Pitch / Roll / Azimuth Indications | | Optional |
| Real-Time Date-Time Stamp | | Yes: Simplified, Extended, DTG Formats |
| Digital Video Recorder with Real-Time Electronic Reticles Detection Capability: Man (1.7x0.5m) / | Stamp | Optional: Comes with removable 32GB microSD card |
| Z Electronic Reticles | | 8+8 Patterns, Easy Zeroing / Calibration |
| | NATO Target (2.3x2.3m) | 1660m / 2250m |
| Hand-Held Configuration | | Yes |
| Conversion to Clip-On (In-Line) Sight | | Yes |
| Tripod-Mountable User Profiles (Configurable) | | Yes |
| User Profiles (Configurable) | | Yes: 8 |
| Automatic/Manual Pixel Masking | | Yes |
| Reset to Factory Defaults | | Yes |
| External Video Feed Protection | | Yes |
| Automatic Power Down Control | | User-Configurable: 10 60 minutes of inactivity |
| Accepted Batteries | | 2 (two) CR123 of Any Type: Lithium / Rechargeable |
| Universal Port | | Video-Out, Remote Control and External Power (4VDC 15VDC) |
| Battery Life on 2x CR123 | | Up to 7 Hours |
| Environmental Protection | | Fully Waterproof |
| Dimensions | | 172 x 60 x 60 mm |
| Weight | | 475 grams |
| Operating Temperature | | -40°C +50°C |
| Warranty | | 7 Years, Limited |
| Made In Canada | | ITAR-Free |

DISCLAIMER. Technical description, certain optical-electronic-mechanical features of the product shown herein and/or some of its parts/components may not precisely represent the actual device and are subject to change without prior notice by the sole discretion of General Startington, and electronics. Dimensions of the product represents measurable size of the body including all optical components attached and in fully folded position. Dimensions so deductions such as optical components attached and in fully folded position. Dimensions expected in a component of additions such as mounting brackets, eyecups, objective length of the product represents measurable size of the body including all optical components attached and in fully folded position. Dimensions several actual many components are components attached and in fully folded position. Dimensions such as mounting brackets, eyecups, objective length of the product represents may not precisely and the product represents and the product represents a product and the product represents a product represents a product represents and the product represents a product represents





PRECISION THERMAL RIFLE SCOPE

TI-GEAR-S650F

| | STANDARD EQUIPMENT: WHAT'S IN THE BOX |
|----|---|
| 1 | Thermal Imaging Sight |
| 2 | Long Eyerelief Rubber Eyecup (Attached) |
| 3 | Front Lens Protective Cover (Attached) |
| 4 | Dual Lever Adjustable Rifle Mount DLM (Picatinny, with fine-tune knobs for tolerance adjustments) |
| 5 | Demist Shield |
| 6 | USB Power Cable |
| 7 | Video-Out Cable |
| 8 | Soft Carrying Pouch |
| 9 | User Manual |
| 10 | Quick Reference Card |
| 11 | 7-Year Warranty with Activation Form |
| 12 | Waterproof Hard Carrying Case |
| 13 | Cleaning Kit (3-in-1 Multi-Pen + Cleaning Cloth) |

^{*} Batteries not included

| | OPTIONAL EQUIPMENT |
|---|--|
| Α | Universal Remote Control Unit TRC-120 (Comes with connection cable) |
| В | Universal Multi-Voltage Battery Pack MVP-240 (Comes with connection cable) |
| С | Built-In Digital Video Recorder GS-DVR-INT (Comes with 32GB microSD card and SD adapter) |
| D | External Digital Video Recorder GS-EDVR (Comes with set of cables and 32GB SD card) |
| E | MTAR [™] -HUD Heads Up Display (streams video directly from the unit; equipped with built-in DVR, GPS and Integrated 9-Axis Absolute Orientation HUD) |
| F | Portable Head-Mounted Display HMD-800-MOD (streams thermal video directly from the device, comes with connection cable) |
| G | Integrated 9-Axis Absolute Orientation HUD (Heads-Up Display), 3-Axis Sensors for Compass Reading, Inclinometer/Pitch Reading, and Level/Roll Reading |
| Н | Heavy-Duty Quick Release Rifle Mount MAK-QR-BLASER (Blaser, Adapter included) |
| I | Heavy-Duty Quick Release Rifle Mount MAK-QR-PICATINNY (PICATINNY, Adapter included) |
| J | Heavy-Duty Rifle Mount MAK-PICATINNY (PICATINNY, Adapter included, Allen Key Included) |
| K | Adapter for MAK Mount: Regular Length (ADAPTER-REG) or Extended Length (ADAPTER-EXT) |
| L | Clip-On Adapter COA |
| М | Day Scope Adapter Clamp for COA for direct mounting onto daytime optics, CO-DSA (various sizes available) |