

Working Hard for the Hard Working®

CrownMats.com | 1-800-MAT-LINE | 48 HOUR SHIPPING



Electrically Conductive Deck Plate

SKU: 930

Electrically Conductive Deck Plate quickly drains static charge to protect components and equipment. Static dissipative surface ideal for industrial environment. Deck plate top surface enhances traction and security. As an anti-static mat, Electrically Conductive Deck Plate will help retain safety and security in the office. PVC foam backing allows good anti-fatigue relief while standing.

FEATURES

- Resistivity of 10^6 ohms per square
- Beveled edges for improved safety
- Stock mats include ground cord, which can be connected to an electrical outlet. It is recommended to use one cord per 10 feet

APPLICATIONS

Provides a heavy duty solution for dry areas e.g.: Computer work station and terminal, Sensitive electronic equipment and Electrical room.



Stock mats include one grounding cord. For custom cuts and full rolls, the grounding cords must be purchased separately. It is recommended that there be one grounding cord for every 10' of matting.

75' rolls are manufactured to a tolerance of $\pm 1"$.

Full rolls are not beveled on ends unless specified. Rolls with beveled ends are priced as custom cuts.

Additional Information

| | |
|---------------------|----------------------------|
| Sizes | 2' x 3', 3' x 5', 3' x 12' |
| Rolls | 3' x 75' |
| Colors | Black |
| Thickness | 9/16" |
| Total Customization | No |
| Warranty | 1 year |

Technical Data

| | |
|--------------------------------|---|
| Material: | Extruded vinyl with deck plate surfac |
| Surface electrical properties: | 1/100 sec from 20,000 volts to harmless |
| Surface resistivity: | 106 ohms |
| Surface abrasion | <.5 gram loss ASTM-D-4060 |
| Backing durometer: | 45 \pm 10 ASTM-D-2240 |
| Backing resilience: | STM-D-2632 |

