



AcryliStrip®

Heavy Duty Speed Stripper

DESCRIPTION

A highly effective, fast acting floor finish stripper that will emulsify aged, burnished, and built-up finishes almost instantly. May be used as a no-scrub stripper or with a rotary floor machine and pad depending on the concentration of the product and the condition of the floor.

DIRECTIONS

Sweep or dust mop the floor to remove any debris. Dilute stripper 1:4 – 1:10 with cold or mildly warm water. The optimum use-dilution will depend on the age and buildup of the floor finish. Apply the stripping solution liberally using a mop or automatic scrubber. Allow to stand for at least 3 - 5 minutes. Do not allow the stripper solution to dry. Be sure to completely cover floor to baseboards. Scrub with a rotary floor machine or automatic scrubber equipped with stripping pads. Pick-up the solution and old finish with a wet vacuum, automatic scrubber, or clean mop. Rinse thoroughly with clean cold water.

NOTE: Wet floor may become extremely slippery. Be sure to keep pedestrian traffic away from floor until thoroughly dry.

PRODUCT SPECIFICATIONS

Active Ingredients:	14.0 ± 0.5%	Emulsification:	Excellent
Color:	Light amber	Detergency:	Excellent
Odor:	Sassafras	Rinsability:	Excellent
pH:	12.2 - 12.7	Flash Point:	None (waterbased)
Viscosity:	Slightly viscous	Biodegradability:	Complete
Foam:	Low	Storage/Stability:	2 years
Abrasives:	None	Weight per Gallon:	8.68 lbs./gal.
Solubility:	Complete with water	Freeze / Thaw Stability:	Keep from freezing