



AcryliWax® Plus

High Gloss Floor Finish



AcryliWax® Plus is an easy to use, high solids acrylic floor finish designed for high traffic areas where high gloss and durability are critical, such as classrooms, healthcare facilities, office buildings, hallways, entrances, and hospitals. Dries to a hard, durable finish that withstands high traffic yet responds well to low or high-speed spray buffing.

DIRECTIONS

Preparation

If stripping is necessary, use AcryliStrip® and follow the directions accordingly. Follow with a thorough rinsing and allow floor to dry completely. If stripping is not necessary; sweep up loose dirt and dust. Clean with a quality cleaner to remove dirt and oils. Follow with a thorough rinsing and allow floor to dry completely.

Finishing

Spread a liberal coat of finish evenly across the floor with a clean mop or applicator. Allow each coat to dry at least 30 minutes before applying the next coat. Four coats is ideal initially, depending on the condition of the floor and desired gloss.

Maintenance

The floor may be maintained using NeutraMax® and damp mopping regularly. Spray buffing with AcryliBuff® or mop-on restoring may also be done after sweeping up loose dirt and dust. Follow directions for each product accordingly.

Dry/Recoat Time: 30 minutes minimum

Recommended Coats: 4 to 5

PRODUCT SPECIFICATIONS

Type:	Modified acrylic	Removability:	With conventional strippers
Non-volatile solids:	22.0±0.5%	Detergent Resistance:	Excellent
Color:	Milky white	Waterspot Resistance:	Excellent
Odor:	Mild	Heel Mark Resistance:	Excellent
pH:	8.5 - 9.0	VOC Content:	0.39 lbs./gal.
Dry/Recoat Time:	45 minutes min.	Storage/Stability:	2 years
Slip Resistance:	0.5 min. by ASTM D2047	Freeze/Thaw Stability:	Keep from freezing
Gloss:	90+ specular	Weight per Gallon:	8.58 lbs./gal.
Leveling:	Excellent	Coverage:	2000-2500 ft ² per gal.
Buffability:	Spray buff or restorer		

JaniSource, LLC 478 Bramblewood Heights Rd, Marietta, Ohio 45750