

## AcryliStrip®

Fast-Acting Floor Wax Stripper



Use as directed on vinyl flooring, linoleum, terrazzo, concrete, and slate.

AcryliStrip<sup>®</sup> is a highly effective, fast acting floor finish stripper that will emulsify aged, burnished, and built-up finishes almost instantly. May be used as a no-scrub stripper or with a rotary floor machine and pad, depending on the concentration of the product and the condition of the floor.

## DIRECTIONS

**1.** Sweep or dust mop the floor to remove any debris.

2. Dilute stripper 1:4 – 1:10 with cold or mildly warm water. The optimum use-dilution will depend on the age and buildup of the floor finish.

3. Apply the stripping solution liberally using a mop or automatic scrubber Allow to stand for at least 3 – 5 minutes. Do not allow the stripper solution to dry. Be sure to completely cover floor to baseboards.

**4.** Scrub with a rotary floor machine or automatic scrubber equipped with stripping pads.

**5.** Pick-up the solution and old finish with a wet vacuum, automatic scrubber, or clean mop.

6. Rinse thoroughly with clean cold water.



Active Ingredients: Color: Odor: pH: Viscosity: Foam: Abrasives: Solubility: 14.0 ± 0.5% Light amber Sassafras 12.2 - 12.7 Slightly viscous Low None Complete with water

Emulsification: Detergency: Rinsability: Flash Point: Biodegradability: Storage/Stability: Weight per Gallon: Freeze / Thaw Stability: Excellent Excellent Excellent None (waterbased) Complete 2 years 8.68 lbs./gal. Keep from freezing

## JaniSource, LLC 478 Bramblewood Heights Rd, Marietta, Ohio 45750