


PILE-UP®



TRAFFIC LANE AND BONNET CLEANER

Cleans and brightens carpets efficiently with low moisture



Pile-Up® TLC is specially formulated for bonnet buffing as an interim system that is fast, uses low moisture, and dries quickly to maintain a high quality appearance level. An excellent prespray on high traffic lanes of carpet prior to extraction cleaning. The built-in emulsifier dissolves the stubborn greasy soil for deep cleaning, and more importantly, reduces the resoiling rate of the carpet. Does not contain any optical brighteners. This product cleans carpets faster and more efficiently than any product on the market today. It is most effective on carpets that have been previously treated with a mill-applied fluorochemical stain-resistant treatment.

DIRECTIONS FOR BONNET CLEANING

Vacuum carpet thoroughly. Test carpet for colorfastness in an inconspicuous area before any method of cleaning. If the carpet is stain treated, it is not necessary to spot clean prior to cleaning. If the carpet is untreated, spot clean first. Always dilute product before use. For heavily soiled areas dilute 1:10 (13 oz. per gallon of water), for moderate soiled areas, 1:20 (6 ½ oz. per gallon of water).

First Method: Prespray- dilute product in sprayer and spray over soiled areas. Allow to dwell 5 minutes then follow up with the extraction method.

Second Method: Bonnet Buffing—For lightly soiled carpets or rugs, dilute one part product to 16 parts water (8 oz. per gallon of water) and add to pump up sprayer. Prespray the carpet and bonnet until wet to touch of the hand, then rotary bonnet buff. Submerged Method— for heavily soiled areas, and medium drying time (20-30 minutes) dilute 8 oz. Per gallon of water in a wringer bucket, submerge bonnet, wring out thoroughly then proceed to buff with rotary machine. For greater results, use two buckets and two bonnets. One for rinsing and the second for cleaning solution.

Third Method: Use rotary machine with a solution tank. Pour the diluted prespray into the tank, release through a flow-thru bonnet driver into the bonnet and proceed to buff. Use caution to not overwet the carpet with solution.

DIRECTIONS FOR TRAFFIC LANE CLEANING

Prior to extraction cleaning the carpets, Apply PileUp TLC at 2-4 oz per gallon of water and spray it on the traffic lane and heavily soiled areas, with a small garden type sprayer.

PRODUCT SPECIFICATIONS

Active Ingredients:	35.0 ± 0.5%	Chlorinated Solvents:	None
Color:	Water Clear	Emulsification:	Excellent
Odor:	Spring mist	Detergency:	Excellent
pH:	9.5 - 10.0	Rinsability:	Excellent
Viscosity:	Water thin	Biodegradability:	Complete
Foam:	Low	Storage/Stability:	2 years
Petroleum Distillates:	None	Weight per Gallon:	8.59 lbs./gal.
Solubility:	Complete with water	Freeze / Thaw Stability:	Keep from freezing

JaniSource, LLC 478 Bramblewood Heights Rd, Marietta, Ohio 45750