



# AcryliShine®

## Anti-Slip Gloss Restorer



Creates anti-slip surface ideal for use in nursing homes, supermarkets, hospitals, schools and other public areas.

**SAFE FOR USE ON**  
vinyl flooring  
linoleum  
terrazzo  
concrete

AcryliShine® is ideal for use with any high speed maintenance program. Regular use of this product keeps floors looking great day after day. Special proprietary ingredients bond to the surface of the floor to create an anti-slip surface, making it ideally suited for nursing homes, supermarkets, hospitals, schools and other public areas. This product effectively cleans the floor and restores floor finish. Highly concentrated for economical use dilutions, it can be mopped on or used through an automatic scrubber. Once the product dries to a haze, use a high speed burnisher to “pop” the gloss to a brilliant shine.

### DIRECTIONS

#### Cleaning/Maintaining

Dust mop all flooring and remove gum and adhesives. Add 8 ounces of AcryliShine® to clean water in the solution tank of the auto-scrubber or mop bucket. Auto-scrub or mop on all flooring using overlapping passes. If auto-scrubbing, dispense, agitate, and pick up the solution. Pick up any puddles with a clean damp mop. Allow to dry thoroughly. Burnish with a high speed floor machine (1500 RPM or Greater).

#### Floor Restoring

Dust mop all flooring and remove any gum or adhesives. Damp mop or auto-scrub floor with NeutraMax® following label directions. Dilute 1 part AcryliShine® to 4 parts cool water in a mop bucket or auto-scrubber. Apply a thin, even coat on the surface. Do not pick up solution. Allow to dry thoroughly. Burnish all flooring with a high speed buffer to restore the floor to the ultimate “wet look” shine with a burnishing pad.

**Note: Don't allow restorer solution to remain in the auto-scrubber tank. Drain and rinse.**

### PRODUCT SPECIFICATIONS

<b>Type:</b>	Modified acrylic	<b>Removability:</b>	With conventional strippers
<b>Non-volatile solids:</b>	22.0±0.5%	<b>Detergent Resistance:</b>	Excellent
<b>Color:</b>	Milky white	<b>Waterspot Resistance:</b>	Excellent
<b>Odor:</b>	Mild	<b>Heel Mark Resistance:</b>	Excellent
<b>pH:</b>	8.5 - 9.0	<b>VOC Content:</b>	0.39 lbs./gal.
<b>Dry/Recoat Time:</b>	45 minutes min.	<b>Storage/Stability:</b>	2 years
<b>Slip Resistance:</b>	0.5 min. by ASTM D2047	<b>Freeze/Thaw Stability:</b>	Keep from freezing
<b>Gloss:</b>	90+ specular	<b>Weight per Gallon:</b>	8.58 lbs./gal.
<b>Leveling:</b>	Excellent	<b>Coverage:</b>	2000-2500 ft² per gal.
<b>Buffability:</b>	Spray buff or restorer		

**JaniSource, LLC 478 Bramblewood Heights Rd, Marietta, Ohio 45750**