

EU declaration of conformity according to PPE Regulation (EU) 2016/425 - RETRACTABLE TYPE FALL ARRESTER

Manufacturer: PROTEKT, Starorudzka 9, 93-403 Lodz, Poland, and Distributor: FREMST AB, BOX 137, 242 22 HÖRBY, owner of Litewear AB, Benarp 6116, 242 95 HÖRBY confirms that the listed personal



protective equipment (PPE) complies with the guidelines of the PPE Regulation (EU) 2016/425; Where the harmonized standard EN 360:2002. has been implemented into national law, the national standard is also applicable. The PPE listed below has been tested by independent testing laboratories and assessed and certified by the specified notified body. You can find the corresponding certificates using the link below. This declaration of conformity is issued under the sole responsibility of the manufacturer.

Product name:	DWR040S
Product line:	Fall protection
General product properties:	Retractable type fall arrester, max 140 kg work load
Product characteristics:	Double retractable type fall arrester with polyester webbing equipped with connector with swivel. Exclusive vertical use
Product group:	Fall protection - Retractable type fall arrester
Production serial no:	00000001 to 00000001
EN standard:	EN 360:2002 PPE Regulation (EU) 2016/425
Usage:	Constant use
General instructions:	Instructions and information from the manufacturer are included with the product.

Risk category (PPE regulation): CATEGORY III PPE: Life-threatening risk, protects against the risk of death



Product description

DWR040S is a lightweight fall arrest device with two webbings, designed for work requiring frequent changes of the attachment point. The locking mechanism is located in a durable housing with a swivel in the upper part of the device. No need for an additional safety shock absorber. The DWR040S self-locking device is a component of individual fall protection equipment

Article no:	DWR040S
Product SKU:	LW-1004123
Color:	Black
Material house:	Composite
Material hardware:	Stainless steel
Usage:	Vertical use - Protection for 1 person, max 140 kg work load
Length:	2 m
Max braking force:	6kN
Min. static strength:	15kN
Tape width:	18.5mm

IMPORTANT:

If the full body harness are used improperly or are permanently modified in any way (e.g. removal of individual parts such as side threads, hardware, etc.), any liability claim against the manufacturer will expire. The corresponding technical data sheets are deposited at the address mentioned above.

Notified body:

PRS - No.1463, Polski Rejestr Statków S.A. al. gen. Józefa Hallera 126,
80-416 Gdańsk performed the EU type-examination (Module B) and issued the EU
type examination certificate: CW/PPER/69/12/2020

The PPE is subject to the conformity assessment procedure module D under surveillance of the notified body Apave Exploitation France SAS (n°0082), 6 Rue du Général Audran, 92412 COURBEVOIE cedex, France.

HÖRBY 2023-05-23



Simon Rosengren, CEO & Founder
Fremst AB / Litewear AB

simon@fremst.se
+46 415 22000