## **VETROSPACE XXL**

## PERFECT FOR 10

Our largest pod comfortably fits up to 10 people, making it ideal for meetings and encounters or for when you need plenty of space to spread out and focus on a creative task. This flexible and highly modular soundproof booth is built to last.

VIEW ONLINE →



Plug-and-play solutions



Automated, smart CO2-controlled ventilation



Best-in-class soundproofing



Easy access for people with mobility limitations



Superior indoor air quality with G4 and HEPA H13 filters



Antimicrobial LED Antimicrobial surface lighting nanocoating



ISO 7 indoor air quality performance













## **TECHNICAL SPECS**

**Exterior dimensions** W410 / D310 / H240 cm | W161.4 / D122 / H94.5 in

**Exterior material** LP-laminate

**Interior dimensions** W400 / D300 / H220 cm | W157.5 / D118.1 / H86.6 in

Interior materialAcoustic ECOfelt liningWeight1950 kg | 4300 lbsIndoor surface area12 m² | 129.1 ft²

**Modular sizes** 1–100 m<sup>2</sup>

Installation height >250 cm | >98.5 in

requirement

Fire safety UL 723: Class A-C (surface)

ASTM E648: Class 1 (flooring)

**Electrical safety** IEC 60335-1:2020

UL 962 (E514776)

Seismic safety Special SEISMIC Certification (2019-0176-COC-01-00),

International Building Code (IBC) 2018 (23.02.2021), California Building Code (CBC) 2019 (23.02.2021)

Patents US PATENT: 11.492.815 B2

International patents (FI, US, EP, CH, HK, RU)

**Door** Patented sliding door

Glass thickness 16.7 mm | 0.66 in sound-control safety glass

**Sound reduction** Ds: Class A (ISO 23351-1) 43-46dB Rw Lab. STI: 0.03 **Ventilation system** Advanced two-stage air filtration (coarse and HEPA 13)

Air flow Max. 180 l/s

**Pressure** Positive air pressure

**Cooling/heating** Optional

**Lighting** VLD antimicrobial LED

**Surface treatment** Photocatalytic antimicrobial nanocoating

Power supply 110-240 VAC / 16 A / 50-60 Hz Power 150 W average, 800 W maximum

**Power sockets** 4 as standard







