VETROSPACE XL

GREAT FOR A TEAM OF 8

Enjoy exceptional sound insulation and air quality in our second-largest pod, which offers plenty of space for up to eight and also works as a cozy private space. You can design and furnish it according to your needs from a variety of options.

VIEW ONLINE →



Plug-and-play



Automated, smart CO2-controlled ventilation



soundproofing



Easy access for people with mobility



Superior indoor air quality with G4 and **HEPA H13 filters**







nanocoating

ISO 7 indoor air quality performance













TECHNICAL SPECS

Exterior dimensions W310 / D310 / H240 cm | W122 / D122 / H94.5 in

LP-laminate **Exterior material**

Interior dimensions W300 / D300 / H220 cm | W118.1 / D118.1 / H86.6 in

Acoustic ECOfelt lining Interior material

1600 kg | 3520 lbs Weight Indoor surface area 9 m² | 96.8 ft²

1–100 m² **Modular sizes**

Installation height >250 cm | >98.5 in

requirement

Fire safety UL 723: Class A-C (surface)

ASTM E648: Class 1 (flooring)

IEC 60335-1:2020 **Electrical safety**

UL 962 (E514776)

Special SEISMIC Certification (2019-0176-COC-01-00), Seismic safety

International Building Code (IBC) 2018 (23.02.2021), California Building Code (CBC) 2019 (23.02.2021)

US PATENT: 11.492.815 B2 **Patents**

International patents (FI, US, EP, CH, HK, RU)

Patented sliding door Door

16.7 mm | 0.66 in sound-control safety glass Glass thickness

Ds: Class A (ISO 23351-1) 43-46dB Rw Lab. STI: 0.03 **Sound reduction Ventilation system** Advanced two-stage air filtration (coarse and HEPA 13)

Air flow Max. 120 l/s

Positive air pressure **Pressure**

Cooling/heating Optional

VLD antimicrobial LED Lighting

Surface treatment Photocatalytic antimicrobial nanocoating

110-240 VAC / 16 A / 50-60 Hz Power supply 100 W average, 550 W maximum **Power**

Power sockets 4 as standard









