

Med**⊗**Scan

1300 736 330

www.medescan.com.au

instruction videos. You can also scan the QR code for instant acc

Life cycle of product is three years VER: 351N4FB-20220120-V01

Visit our YouTube channel for our latest easy to follow instructional videos. Simply search for Medescan on YouTube and subscribe to our channel for the latest products and

Med**⊗**Scan

HEARING AID

Instruction Manual Model: JH-351

Please read this user manual thoroughly and

completely before using the product

Safely out of reach from children and pets

-Sarery out or reach from children and pets

Synergy Charger Care

Keep your charger clean. Heat, moisture and foreign
materials can result in poor performance.

-Using the provided cleaning brush keep the charging
ports clear of debris.

Do not use water, solvents or cleaning fluids to clean
the charging ports.

-Keep lid closed as much as possible to avoid dust
and debris build up.

-Store your charger in a clean and dry location, i.e. a
dresser or shelf rather than the bathroom or kitchen.

To ensure the longest life of your rechargeable
hearing aids batteries and the batteries in the
charger:

-Fully charge hearing aids batteries every night.

are inserted into the charging port Dead battery Reposition your hearing aids in the port with the earbud resting Red blinking LED by charging port Fault occurred illuminated

difficult

 Rephrase rather than repeat the same words;
different words may be easier to understand
 Minimize distractions while speaking X. NORMALIZED SYMBOLS Follow operating instructions B type applied part nce with Directive Ø 2002/96/EC (WEEE) Complies with the European Medical Device Directive (93/42/EEC and amended Directive 2007/47/EC. Notified Body is SGS Belgium.

Manufacturer information

Warning/ Danger: Improper use might cause serious injuries.

cause serious injuries.
IP code of the device: this device's grad of against ingress of solid foreign object – the access probe of ≥ Ø 12.5mm shall not penetrate; the grade of waterproof is vertically falling drops shall have no harmful effects.

Permissible storage and transport

temperature and humidity Permissible operating temperature

and humidity

Date of manufacture

C €₁₆₃₉

رسآ

SN

À

IP21

Ø

XII.GUARANTEE

Pic. tips: -or You

To refresh LEDs, remove a hearing aids from the charging port for 3 seconds and then reinsert it into the charging port. Both the charging port LEDs and the on-board battery LEDs will illuminate after turn it on. While charging cordless, no LEDs Please review the following simple communication **For You

*Move closer to and look at the speaker

*Sit face-to-face in a quiet room

*Try different locations to find the best place to listen

*Minimize distractions

**Background noises may be frustrating at first; **Background noises may be frustrating at first; remember, you have not heard them for a while *Let others know what you need; keep in mind that people cannot "see" your hearing loss *Develop realistic expectations of what your hearing aids can and cannot do **Better hearing with hearing side is a located with *Better hearing with hearing aids is a learned skill combining desire, practice and patience For Your Family and Friends
Your family and friends are also affected by your
hearing loss. Request that they:
"Get your full attention before beginning to speak
"Look at you or sit face-to-face in a quiet room
"Speak clearly and at a normal rate and level;
shouting can actually make understanding more
difficult •Rephrase rather than repeat the same words; different words may be easier to understand more

with the earpuu resu in charger reservoir. Remove the hearing aids from the charging port, wait until the LED turns off, reinsert. If the red blinking LED persists contact your hearing professional.

Service and Repair If, for any reason, your hearing aids and charger do not operate properly, do NOT attempt to fix it yourself. Not only are you likely to violate any applicable warranties or insurance, you could easily cause further damage. Should your hearing aids and charger fail or perform poorly, check the guide on the next page for possible solutions. If problems continue, contact your hearing professional for advice and assistance. Many common problems may be solved in your hearing professional's office or clinic. Dead Hearing Blocked earbud/tubing Clean or replace wax guard as needed Crimped tubina Contact your hearing professional No LED Incorrect orientation Connect the micro USB to your charger and plug it into the wall. The on-board battery LEDs indicator when hearing aids on-board pattery LEUs will turn on for a few seconds to indicate connection to the power source. If they do not, contact your hearing professional.

Troubleshooting Guide SYMPTOM POSSIBLE CAUSES Blocked tubing/earbud

Hearing change Debris buildup Restart required

Not Loud

Inconsistent Performance

Unclear. Performance

Hearing aids

whistling in the

Dead Hearing Charge required

Dead battery

IX.TECHNICAL SPECIFICATION

OG50 MAX Gain

EQ Input Noise

Rated Volatage Operating temperature/humidity

Notes:

ΧI

Frequency Range Battery Current

Total Harmonic Distortion

Storage temperature/humidity

JH-351N ≤115+3

≤42+3dB

≤7%+3%

This hearing aid is produced under the strict quality system of Huizhou JINGHAO Medical Technology Co.,Ltd.

The device fulfils the provisions of the EC directive 93/42/EEC (Medical Device Directive)

and the Harmonize Standard as IEC 60601-1, IEC 60601-2-66, IEC 60118-7, IEC 60118-13, EN ISO 10993-1/-5/-10 and EN ISO 14971.

MAINTENANCE, STORAGE AND DISPOSAL

≤29dB+3dE

400Hz-4500Hz

≥30%RH, ≤75%RH

-10°C~+55°C(14°F-131°F), ≥10%RH, ≤90%RH

Enough

SOLUTIONS as needed
Contact you hearing professional Clean both microphone and receiver with brush Blocked tubing/ earbud Restart required

Place in charger until charging begins and remove -this will power cycle your hearing aids Clean or replace wax guard as needed Place in charger until charging begins and remove-this will power cycle your hearing aids Blocked tubing/ earbud Clean or replace wax guard as needed Defective hearing aids Contact your hearing professional Place in your charger the LEDs stop blinking and become solid

Turn off the hearing aids. Reposition your hearing aids in the port with the earbud Incorrect orient ation resting in the charger reservoir. Confirm that the charging LED begins to glow.

Your charger's on-board battery has died. Plug your charger in. If you do not have the cord with you, push and hold the hearing aids's rocker switch for 3 seconds to turn it off. This will conserve the charge in your hearing aids. VIII.TIPS FOR BETTER COMMUNICATION Your hearing professional will recommend an appropriate schedule to help you adapt to your new hearing aids. It will take practice, time and patience for your brain to adapt to the new sounds that your hearing aids provides. Hearing is only part of how we share thoughts, ideas and feelings. Reading lips, facial expressions and gestures can help the learning process and add to what amplification alone may miss.

11.3 Disposal

1) We do not authorize any institution or individual to maintain and repair of the product. If you suspect that the products have any questions, please contact the manufacturer or distributor to handle the case. 2) The user must not attempt any repairs to the device or any of its accessories. Please contact the retailer of any of its accessories. I leads contact the research of the repair.

3) Opening of the equipment by una- uthorized agencies is not allowed and will terminate any claim to warranty. warning: No modification of this equipment is allowed! 11.2 Storage
1) If you Do not use it, turn off the hearing aid, take out the batteries, and then put it into the storage case.
2) Do not put the device under the sunshine, high temperature and moist environment or some

We grant you a lifetime guarantee after the date of purchase for two year. Any damage caused by improper handling shall not be covered by the guarantee. Batter and packaging are also excluded from the guarantee. All other damage claims excluded. A guarantee claim must be submitted with the purchase receipt. Please pack your defective instrument well and send with sufficient postage to the distributor.

the

3) Keep the device storage in following environmental ranges:-10~55 ℃, ≤95%RH, 700-1060hPa Please dispose of the device in accordance with directive 2002/96/EC – WEEE (Waste Electrical and Electronic Equ- ipment). If you have any queries, please refer to the local authorities responsible for waste dis- posal.