

Support & Accessories at:  
[www.FlowJoe.com](http://www.FlowJoe.com)



Model- 12V- WXP

Made in the USA from domestic  
and imported parts by GenTap LLC

### Basic Instructions

1. Extend the power cord and check that the inline power switch is OFF before connecting to power. Connect the plug to 12V auto accessory receptacle and check the plug for a red LED light to confirm that you have power.
2. Place the input hose (equipped with stainless mesh screen) into your source.
3. Place the output hose into destination. Use the orange hose clips to secure hoses.
4. Switch the unit on and monitor it for flow. If flow does not start in 10 seconds, switch off and reposition the input line.
5. Your fluid source can be no more than 10 feet lower than the pump itself. This pump can raise fluid up to 10 feet.

**Note:** Flow Rate: Up to 1.5 Gallons per minute.

Some units are equipped with a remote-control A/B keychain switch. The A button is ON and the B button is OFF.

**Uses:** Camping, wash down, fill tanks, radiators, empty plumbing fixtures, fish tanks, remove standing water and more!



## Caution:

**Fluid Types:** Water, mild soaps or detergents, coolant (when cool).  
Always rinse with clean water after use.

**Warning:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

Read online manual before use. Go to: [www.FlowJoe.com](http://www.FlowJoe.com)  
Plug directly into a 12V vehicle outlet or use only approved AC to DC converter.  
Operate for up to 30 minutes at a time with a 10-minute rest period in-between.  
Always use caution around electricity and water. Keep any AC adapter away from water and away from you while operating.

**Troubleshooting:** If the pump does not run, check 12V connection plug for a red LED light. If red light does not come on, check the fuse located inside the socket. To do so, unscrew the plug tip by hand and check the internal 5-amp fuse. Input port is equipped with a mini screen. If you are having trouble starting flow, remove hose and check screen for debris.