



For a complete range of KOATE products, product data sheets, stockists and useful links, please visit our website:

www.koate.co.uk



Scan for latest news

7A Vanguard Way, Battlefield Enterprise Park, Shrewsbury. SY1 3TG

WWW.KOATE.CO.UK Info@koate.co.uk An exclusive range of high performance

INTERIOR/EXTERIOR WOOD PROTECTION



PREMIUM WOOD TREATMENTS, FOR A LONGER LIFE

Inspired by the technological advances in the coating industry, our range of coatings offers a dynamic choice of colours and finishes.

Our finishes are a blend of natural oils which give natural elegance to wood - with a timeless, classical beauty and enduring warmth.

Our passion for finishes, gained through 30 years experience working with top designers in the industry, means we bring far more than a wood coating.

Koate can create a bespoke colour to fit in with your project design and theme. Working with our in-house colourist, we'll help you find the ideal match for you - and we also offer a full range of standard colours. Not only is our wood coatings suitable for wood surfaces but also for other surfaces such as Valchromat and Honext.

Our journey with you will go beyond the perfect finish and colour for your wood surface. Whether you seek refreshingly individual, charmingly rustic, sustainable or industrial, we'll work with your entire design concept and help you choose a finish that is as practical and durable as it is stylish.





Colours and protects your wood doors from daily wear & tear in one coat



Koate



0% voc

One Coat Door Oil is a two component one-layer Hardwax oil that can be used for the protection of interior wood doors. The oil is the result of a unique blend of natural oils and hard waxes without addition of solvents and enhances the natural look and feel of the wood.

- 0% VOC's, NO volatile organic compounds
- High coverage per litre
- Provides colour and protection in One Coat
- · Easy to apply to all wood types
- No overlaps
- Extended pot life when mixed, 2 component
- Easy to maintain



Scan for more information on this product







PURE



SILKWORM



MOCHA



WHITE

APPLICATIONS: All interior wood surfaces including HDF & MDF.

COVERAGE: 40-50m²/litre.

Drying time: 1. Depending on the substrate and drying conditions (temperature, humidity, ventilation) the surface is touch dry between 1-2 hours. 2. Fully dry in 24 hours. 3. Fully cured in 7 days. Adhere to curing time to allow effectiveness of protection.

Available in: 20ml, 100ml, 500ml, 1 litre.





ONE COAT WOOD OIL

Colours and protects your wood surfaces from daily wear & tear in one coat



0% voc

One Coat Wood Oil is a two component one-layer Hardwax oil that can be used for the protection of all interior wood surfaces.

The oil is the result of a unique blend of natural oils and hard waxes without addition of solvents and enhances the natural look and feel of the wood.

- 0% VOC's, NO volatile organic compounds
- · High coverage per litre
- Provides colour and protection in One Coat
- Easy to apply to all wood types
- No overlaps
- Extended pot life when mixed, 2 component
- · Easy to maintain



Scan for more information on this product



APPLICATIONS: All interior wood surfaces including HDF & MDF.

COVERAGE: 40-50m²/litre.

Drying time: 1. Depending on the substrate and drying conditions (temperature, humidity, ventilation) the surface is touch dry between 1-2 hours. 2. Fully dry in 24 hours. 3. Fully cured in 7 days. Adhere to curing time to allow effectiveness of protection.

Available in: 20ml, 100ml, 500ml, 1 litre.





ONE COAT **WORKTOP OIL**

Colours and protects your wood worktops from daily wear & tear in one coat



0% VOC

One Coat Worktop Oil is a two component one-layer Hardwax oil that can be used for the protection of interior wood.

The oil is the result of a unique blend of natural oils and hard waxes without addition of solvents and enhances the natural look and feel of the wood.

- 0% VOC's, NO volatile organic compounds
- High coverage per litre
- Provides colour and protection in One Coat
- Easy to apply to all wood types
- No overlaps
- Extended pot life when mixed, 2 component
- · Easy to maintain



Scan for more information on this product











PENNY BROWN

PURE

SILKWORM

MOCHA

WHITE

APPLICATIONS: All interior wood surfaces including HDF & MDF.

COVERAGE: 40-50m²/litre.

Drying time: 1. Depending on the substrate and drying conditions (temperature, humidity, ventilation) the surface is touch dry between 1-2 hours. 2. Fully dry in 24 hours. 3. Fully cured in 7 days. Adhere to curing time to allow effectiveness of protection.

Available in: 20ml, 100ml, 500ml.



COLOUR BASE

Pre-colours your wood to create more shades of colour



Colour Base is an environmentally friendly stain based on a unique Cellular Saturated Anchoring (CSA) technology containing nano minerals structures and micro-pigments. This technology enables the applicator to apply the stain without overlapping.

- 0% VOC's, NO volatile organic compounds
- · Easy to apply to all wood types
- No overlaps
- Good colour fastness
- Water based



Scan for more informatio on this product





CREATIVE BASE

Tones your wood to create more depths of colour

0% voc

Creative Base is an environmentally friendly stain based on a unique Cellular Saturated Anchoring (CSA) technology containing nano minerals structures and micro-pigments. This technology enables the applicator to apply the stain without overlapping.

- 0% VOC's, NO volatile organic compounds
- Easy to apply to all wood types
- No overlaps
- Good colour fastness



Scan for more information on this product



APPLICATIONS: All wood surfaces.

COVERAGE: 8-14m²/litre.

Drying time: Depending on the drying conditions, a minimum of 2 hours before finishing coat can be applied using ONE COAT WOOD OIL 2C or WOOD VARNISH 2C from the Koate range.

Available in: 100ml, 1 litre,

APPLICATIONS: All wood surfaces.

COVERAGE: 8-14m²/litre.

Drying time: Depending on the drying conditions, a minimum of 2 hours before finishing coat can be applied using ONE COAT WOOD OIL 2C or WOOD VARNISH 2C from the Koate range.

Available in: 100ml, 1 litre,



WOOD VARNISH 2C

Colourless and protective finish with abrasion and water



0% VOC

Wood Varnish 2C is an indoor protective and decorative varnish for all kind of wood-types including MDF and similar surfaces combining a perfectly deep look, emphasizing the natural aspect of the wood, with an outstanding resistance. Available in Satin, Matt and X-Matt.

- 0% VOC's, NO volatile organic compounds
- · Protects, decorates and waterproofs
- No overlapping
- · Hides small scratches and defects
- No discolouration due to UV exposure
- · Easy to apply
- Durable
- Odourless
- 2 Component
- X-Matt = Invisible Look



Scan for more information on this product



SATIN

MATT

X-MATT

APPLICATIONS: All interior wood surfaces including HDF & MDF.

COVERAGE: 18m2/litre.

Drying time: Depending on the substrate and drying conditions (temperature, humidity, ventilation) the surface is touch dry in 5 hours. Fully dry in 12 hours. Fully cured in 7 days. Adhere to curing time to allow effectiveness of protection.

Available in: 1 litre, 5 litre.





HYDROGUARD OUTDOOR WOOD PROTECTION

Durable protection for exterior wood surfaces



0% voc

Hydroguard Outdoor Wood Protection is a waterborne breathable and durable protector especially designed for the finishing and treatment of (mainly) exterior wood. Enhances the dimensional stability and durability of the wood due to the hydrophobic character of HydroGuard.

- 0% VOC's, NO volatile organic compounds
- Hydrophobic and breathable
- Antifungal properties
- Provides colour and protection in One Coat
- · Optimal UV protection
- Easy to apply to all wood types
- Easy to maintain
- Quick drying



Scan for more information on this product

- DECKING FURNITURE FENCES CLADDING GATES
- WINDOWS AND DOORS ALL EXTERIOR WOOD SURFACES



APPLICATIONS: All exterior and interior wood surfaces including HDF & MDF.

COVERAGE: 50-100g/m², depending on porosity of surface applied to.

Drying time: 1. Depending on the substrate and drying conditions (temperature, humidity, ventilation). 2. Check water-repellence after 24 hour drying time. 3. If water-repellence is not sufficient a second layer can be applied. 4. Avoid water contamination on the treated surface during above mentioned drying times.

Available in: 100ml, 500ml, 1litre.