

BESANTEK Thermocouple Thermometer Datalogger is widely applied to laboratory fields, food industry, medical application, pharmaceutical industry, industrial application, environmental protection areas and agricultural research fields.

## Features:

- Adaptive and highly sensitive sensor with fast response and high accuracy.
- 8-Channel datalogging with 8 thermocouple types (K, J, E, T, R, S, N, B).
- 88 manual record capacity.
- Records up to 86400 readings (Automatic).
- Sampling rate: fastest 1/second, from 1 to 240 second can be set.
- Log rate: 2s - 24h.
- BSTSoftware.
- Max., min. and current value.
- Large-screen LCD display.
- Accessories: Instruction manual, K type thermocouple, CD software, carrying case, USB cable and battery.



**RGT-DL104+**

## Technical Specification:

RGT-104+	
Measuring Range	-200 to 1800 °C (-328 to 3272 °F)
Resolution	0.1°C
Accuracy	±1°C ± 0.5%
Sensor Type	K, J, E, T, R, S, N, B
Temperature Channel	8 Channel
Sampling Rate	Fastest 1/sec, from 1 to 240 second can be set
LCD Size	68mmx38mm
Power Source	9V battery x 1
Dimensions	162mm x 95mmx 35mm
Weight	380g

## Accessories



Carrying Case



CD Software



USB Cable



Battery



K Type Thermocouple

## Ordering Information:

- RGT-DL104+: 8-Channel Thermocouple Thermometer DataLogger.