



# MAXAMPS LITHIUM ION BATTERY

MODEL NO: MA-3450-3s-Li-ion-Pack



## CONSUMER APPLICATIONS

- + Robotics
- + Unmanned Aerial Systems (UAS) - Drones
- + RC vehicles

## COMMERCIAL & GOVERNMENT APPLICATIONS

- + Unmanned Aerial Systems (UAS) - Drones
- + Unmanned Ground Vehicles (UGV)
- + Robotics
- + Mobile Energy Storage
- + Vehicles

## TECHNICAL DATA

BATTERY DIMENSIONS - 55 x 19 x 67mm

BATTERY WEIGHT - 144g

BATTERY CAPACITY @ 0.5C RATE - 3.45Ah (3450mAh)

VOLTAGE - 10.8v (NOMINAL/STORAGE); 7.5v (MIN); 12.6v (MAX)

WATT HOURS - 37.26Wh

ENERGY DENSITY @ Nominal Voltage - 259Wh/kg

INTERNAL IMPEDANCE (1KHZ AC TYPICAL) - 9mΩ

STANDARD CHARGE RATE - 1.725A (0.5C MAX)

BALANCE CHARGE RATE - 3.45A (1C MAX)

MAXIMUM CONTINUOUS DISCHARGE - 10A\*

MAXIMUM PEAK DISCHARGE - 25A\*

CYCLE LIFE - Varies per application/usage/care

CELL TYPE - UNPROTECTED (No PCB), Flat Top Positive Terminal

STORAGE TEMPERATURE: -20°C to 50°C, OPERATING TEMPERATURE: -20°C to 60°C

\*Discharging at continuous and peak rates may lower life cycles.

MaxAmps is not liable for damages that may result from any information provided in or omitted from this publication, under any circumstances. The data in this document is for descriptive purposes only and is not intended to make or imply any guarantee or warranty. MaxAmps reserves the right to make adjustments to this publication at any time, without notice or obligation.

For more information on how MaxAmps can assist you with your battery power solution needs, visit us at [www.MaxAmps.com](http://www.MaxAmps.com), email [info@maxamps.com](mailto:info@maxamps.com), or call 509-473-9883.