



MAXAMPS LITHIUM ION POLYMER(LiPo) BATTERY

MODEL NO: MA-5200-6s-Modular-Lipo-Pack



CONSUMER APPLICATIONS

- + Robotics
- + Unmanned Aerial Systems (UAS) - Drones
- + RC vehicles

COMMERCIAL & GOVERNMENT APPLICATIONS

- + Unmanned Aerial Systems (UAS) - Drones
- + Unmanned Ground Vehicles (UGV)
- + Robotics
- + Mobile Energy Storage
- + Vehicles

TECHNICAL DATA

- BATTERY DIMENSIONS - 138 x 45 x 55.5mm
- BATTERY WEIGHT - 736g
- BATTERY CAPACITY @ 0.5C RATE - 5.2Ah (5200mAh)
- VOLTAGE - 22.2v (NOMINAL/STORAGE) ; 18v (MIN) ; 25.2v (MAX)
- WATT HOURS - 115.44Wh
- ENERGY DENSITY @ Nominal Voltage - 157Wh/kg
- INTERNAL IMPEDANCE (1KHZ AC TYPICAL) - 18mΩ
- STANDARD CHARGE RATE - 5.2A (1C MAX)
- BALANCE CHARGE RATE - 26A (5C MAX)
- MAXIMUM CONTINUOUS DISCHARGE - 227.5A (43.75C)
- MAXIMUM PEAK DISCHARGE - 910A (175C)
- CYCLE LIFE - Varies per application/usage/care
- OPERATING TEMPERATURE - 0°C to 60°C
- STORAGE TEMPERATURE - 0°C to 23°C

MaxAmps.com is not liable for damages that may result from any information provided in or omitted from this publication, under any circumstances. The data in this document is for descriptive purposes only and is not intended to make or imply any guarantee or warranty. MaxAmps.com reserves the right to make adjustments to this publication at any time, without notice or obligation.

For more information on how MaxAmps can assist you with your battery power solution needs, visit us at www.MaxAmps.com, email info@maxamps.com, or call 509-473-9883.