EPOXY GROUT HAZE REMOVER

EPOXYOFF









WHAT IT'S FOR

- Effectively removes cured epoxy, urethane and pre-mixed grout haze.
- Perfect for nonabsorbent materials: porcelain and ceramic tile, glazed quarry tile, glass mosaic.
- Eliminates organic stains: grease, wine, coffee and other food stains.
- Effective on the toughest ground-in dirt and residue.

ADVANTAGES

- Gel-like consistency: the formula can be easily applied on vertical surfaces.
- Does not harm surfaces.
- Water-based.
- Pleasant almond scent.
- Biodegradable.

HOW TO USE IT

Wait at least 24 hours after grouting before applying **EPOX**YOFF. Make sure the grout is fully cured. Shake well before use. Apply **EPOX**YOFF directly on the surface with a large, flat paintbrush. Make sure to cover the grout residue and organic stains on horizontal and vertical surfaces. Let sit for 30 minutes. Scrub with an abrasive pad. Use a spatula to remove any remaining residue. For large surface areas, use a floor scrubbing machine fitted with the appropriate pad.

Caution: Test the product and dwell times on a small, inconspicuous area of the surface or loose sample before full application. Do not use on absorbent materials such as natural stone, wood or plastic (polymethyl methacrylate and similar).

Storage temperature: between 41°F and 86°F (5°C and 30°C). Must be applied at temperatures between 41°F and 86°F (5°C and 30°C).

■ EFFECTIVELY REMOVES EPOXY, URETHANE AND PRE-MIXED GROUT HAZE.

• GEL-LIKE CONSISTENCY IDEAL FOR VERTICAL SURFACES.



Coverage:

1QT (0.95 L) up to 108 sq.ft. (10 m²) Coverage rates are indicative.



Packaging:

1 QT (946 ml) 6 plastic bottles per box

REV. 01

Data sheets are subject to change without notice. Revision date: September 2021.

FILA. Because It Works.



TOLL FREE 1-844-FILA123





Recommended by over 200 INTERNATIONAL TOP BRANDS

filasolutions.com