



# DUSTLESS 855 XXL



- ◆ NON-SAG AND SLIP RESISTANCE FOR LARGE AND HEAVY TILES
- ◆ NON-SLUMPING FORMULA ELIMINATES TILE LIPPAGE
- ◆ MAY BE APPLIED UP TO 3/4" (19 MM) THICK ON HORIZONTAL APPLICATIONS
- ◆ EXCEEDS ANSI A118.15TE, A118.4TE AND A118.11

## DLT™ DUSTLESS TECHNOLOGY



- Alleviates most dust
- Less mess to clean up
- Easier to mix
- Easier to spread
- Longer working time
- Uses less water



## DUSTLESS 855 XXL



Merkrete's 855 DUSTLESS XXL LHT Mortar features innovative, patented DLT™ DUSTLESS Technology.

**855 DUSTLESS XXL LHT** is a superior-grade, single-component, non-sag, non-slip, polymer-modified mortar for interior and exterior setting of large and heavy tile and natural stone, and gauged porcelain tile (GPT). It may be applied from 3/32" to 3/4" (2.4 mm to 19 mm) thickness to provide better support under large and heavy tiles and stone. 855 DUSTLESS XXL is used for interior and exterior installations in most residential and commercial floor and wall applications. Innovative DUSTLESS Technology (DLT) produces significantly less dust than ordinary thin sets, promoting cleaner working conditions and reducing mess. It uses less water and is creamier and easy to spread.

### STANDARDS:

- Exceeds ANSI A118.15TE, A118.4TE and A118.11 without the need for additives
- ISO 13007-2

### SUITABLE TILE TYPES

- Brick and thin brick
- Cement-based pre-cast terrazzo
- Impervious porcelain and glass tile
- Natural stone tile
- Vitreous, semi-vitreous and non-vitreous tile: ceramic, mosaic, quarry, cement body tile

### SUITABLE SUBSTRATES:

- Brick masonry
- Cement backer board<sup>1</sup>
- Cement mortar beds
- Cement plaster
- Cement terrazzo
- Ceramic tile and stone
- Concrete
- Concrete masonry
- Exterior grade plywood<sup>2</sup>
- Gypsum wallboard<sup>2</sup>
- Merkrete waterproofing and crack isolation membranes
- Merkrete Fracture Guard Uncoupling Mat

<sup>1</sup> Consult cement backer board manufacturer for installation recommendations and to verify acceptability for exterior use.

<sup>2</sup> Interior use only.

RECOMMENDED NOTCH SIZE		
1/4" x 1/4" 6mm x 6mm	1/4" x 3/8" 6mm x 10mm	1/2" x 1/2" 12mm x 12mm
Ceramics	Quarry Tile, Rough Stone	Large Tile, Marble, Stone
APPROXIMATE COVERAGES		
65-75 Ft <sup>2</sup> 6.0-6.9m <sup>2</sup>	55-65 Ft <sup>2</sup> 5.1-6.0m <sup>2</sup>	35-45 Ft <sup>2</sup> 3.2-4.2m <sup>2</sup>

ORDERING INFORMATION		
Item No.	Color	Size
4321	Gray	50 lbs.
4322	White	50 lbs.

**PAREXUSA**  
Parex USA, Inc., a California Corporation

### Corporate Office

2150 Eastridge Ave • Riverside, CA 92507  
merkrete.com • 866-516-0061  
Tech Support: 800-226-2424