



ULTRATECH
INTERNATIONAL, INC

Ultra-Sidewinder, Small Specifications

Part#	1800, 1801, 1802, 1803, 1804, 1805, 1806, 1807, 1820
Dimensions In. (mm)	System: 39½ x 3 x ¾ (1,003 x 76 x 19) Extension: 13½ x 3 x ¾ (333 x 76 x 19)
Weight	System with endcaps: 1.5 lbs. (0.7 kg) Extension: 0.5 lbs. (0.2 kg)
Load Capacity	2,000 lbs./in ² (140.6 kg./cm ²)
Load Capacity per axle:	32,000 lbs. (14,515 kg.)
Construction	Injection-molded acrylonitrile butadiene styrene (ABS) plastic and injection-molded Santoprene™ vulcanized rubber tabs
Internal channel opening	3/4" (19mm) wide x 3/8" (9.5mm) high
Max. turn per segment	8-10 degrees (approx.)
Operating Temp.	-40°F to 120°F (-40°C to 49°C)

- Assembled units can be coiled with the cord in place, creating a 2-ft (approx.) diameter coil for moving and storage.
- Systems included two (2) end caps. Extensions can be added for increased system length (end caps are not included with extensions). Segments can be removed to create custom lengths in 1.5" increments.
- Modular design allows for easy reconfiguration or repair, even with the cable or cord in place.
- Unit is designed for office and light-industrial use and is designed to be run on flat, stable surfaces. Not intended to span gaps, holes or trenches with any weight load.
- The system is capable of withstanding loads from vehicles with pneumatic tires but not designed to be run over by any equipment or vehicle with rigid wheels.

