

BWNC-1242DDIAE

12MP Dome, H.265(+), TrueWDR, AI DL IVA ePoE 2,7-12mm, BURGaiva , Verpixelung, Kennzeichenerk.

PRODUCT DESCRIPTION

Application:

SANTEC SNC-842-E series is a 8 MP bullet camera with integrated IR-LEDs and it is the perfect solution for all 24/7 indoor and outdoor applications. This IP camera has a weather-proof housing (IP-66) and is vandal-proof (IK10). Thanks to 8 megapixel resolution, the images are very clear hence no detail is undetected. Due to the auto focus lens and the web interface the camera is easy to adjust. The camera comes with features such as 3DNR for noise reduction, Wide Dynamic Range (WDR), PoE and micro-SD card slot, to name but a few.

Technical specifications:

Туре	IP day/night dome AI camera
Decoding / Video / Lens	>>>>DECODING/VIDEO/LENS<<<<
Sensor type	12MP 1/1.7" LowLight CMOS
Max. Picture resolution (pixel)	12 MP (4000x3000 pixel)
Video codec	H.264, H.264+, H.265, H.265+, MJPEG(Substream)
Max. frame rate (fps)	25/30fps@12MP
Number of video streams	5 (1xMain, 4x Sub)
Lens mount	Intern
Iris control	DC
S/N ratio (dB)	< 50dB
Focal length	2,7 - 12 mm / F1.4
Lens type	4x autofocus lens
Angle of view (horizontal)	103°(W)-44°(T)
Angle of view (vertical)	75°(W)?33°(T)
Sensitivity (Lux)	0.003 Lux@F1.2 (color)
Sensitivity (Lux)	0Lux (IR on)

BURG-GUARD GmbH Wormgermühle, 58540 Meinerzhagen, Germany Tel.: +49 2358 905 490, Fax: +49 2358 905 499 BURG-GUARD@burg.biz, www.burg-guard.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

Technical specifications:

reclinical specifications.	
IR cut filter	IR-Cut filter (mechanical)
Shutter (sec.)	1/3 - 1/100,000
MOD (minimum object distance)	0,6m
DETECT-OBSERVE-RECOGNIZ E-IDENTIFY	>DETECT-OBSERVE-RECOGNIZE-IDENTIFY<
DORI max. (Detect-Observe-Recognize-Ident	208m - 83m - 41m - 20m
ify)	
DORI min.	85m - 34m - 17m - 8.5m
(Detect-Observe-Recognize-Ident	
ify)	
Features	>>>>>FEATURES<<<<<<
Digital zoom	16x, adjustable
Day/night mode adjustment	Auto / color / B/W
Automatic gain control (AGC)	Yes
Digital noise reduction (DNR)	3DNR
White balance	Auto / sunny / night / outdoor / manual
Backlight compensation	BLC, HLC, TrueWDR(120dB)
Wide dynamic range (WDR)	120 dB WDR (True WDR)
Mirroring (vertical)	Yes
Picture flip (horizontal)	Yes
Privacy zones	Yes, 8
Region of Interest (ROI)	Yes, 4 zones
Defog function	Yes, digital
ANR (automatic network	Yes (for records)
reproduction)	res (ior records)
• *	>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>
Video analysis IVA via ONVIF Motion	>>>>>Videoanalytics<<<<< Yes
Support license plate recognize	Yes
People counting (IVA+)	Yes
People in Area	Yes
Tripwire (IVA)	Yes
Intrusion (IVA)	Yes
Tampering Alarm	Yes
Scene change (tampering)	Yes
IVA Missing / Added	Yes
Audio detect (IVA)	Yes
Face detect (IVA)	Yes
people mosaik	Yes
Queue Management	Yes
Vehicle detection	Yes
Metadatenerfassung	Yes
Motion detection	Yes, 4 areas
Interface	>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>
BURG-GUARD GmbH Wormgermühle, 58540 Meinerzhagen, Ger Tel.: +49 2358 905 490, Fax: +49 2358 905 BURG-GUARD@burg.biz, www.burg-guard	5 499 BURG GUARD

BURG-GUARD@burg.biz, www.burg-guard.com

Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

Technical specifications:

reonnour speemoutons.	
Camera title	Yes
Video output	Yes
Audio support	Yes
Audio in-/outputs	1/1
Audio codec	G.711a / G.711Mu / AAC / G.726
Alarm contacts I/O	3/2 -> Input: 5mA/5VDC / Output: 1000mA/30VDC
Internal memory	Micro SD (optional), max. 256 GB
Network	>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>
Ethernet connector	RJ-45
Ethernet standards	10/100Base-T
PoE standard	IEEE802.3at, ePoE
ePoE / Long-Range-PoE	Yes, up to 250m (with ePoE switch)
Remote	>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>
Alarm management	HTTP, FTP, SMTP, ONVIF
Schedule	Yes
Management software support	Many VMS
Cloud service	Yes, BURG-WÄCHTER cloud
Smartphone App	BurgCam App
Security features	HTTPS, SSL, IP Filter
Supported protocols	HTTP,TCP,NTP,IPv4,IPv6,DHCP,TELNET, ONVIF, FTP
Supported software standards	ONVIF, PSIA, CGI
Supported browser	Internet Explorer 11, Chrome, Firefox, and more
Edge Recording	NAS(NFS), locall PC, micro SD card, FTP
General	>>>>>>GENERAL<<<<<
Classification	IP67, IK10
Vandal-proof	Yes
Heater	No
Installation	Wall and ceiling mount
3 axis	yes
Camera mounting	Screw mounting
Housing colour	White / black
Housing material	Metal / Plastic
Integrated IR-LEDs	Yes, Smart IR, off, manual
Wavelength LED	850 nm
IR-LED illuminant	3
IR distance (m. ca.)	40
· · · ·	24VAC , 12VDC, PoE
Voltage	
Max. Power consumption (watt)	<19,3 (24Vac) < 15.2 (12Vdc) -30 to +60
Operating temperature (°C)	
Storage temperature (°C)	0 to +60
Rel. humidity (%)	Max. 95, non-condensing
Dimensions ØxH (mm)	340.1 mm × 138.5 mm × 134 mm
Weight	1,5 kg
Identifier	CE, RoHS
BURG-GUARD GmbH Wormgermühle, 58540 Meinerzhagen, Ge Tel.: +49 2358 905 490, Fax: +49 2358 90 BURG-GUARD@burg.biz, www.burg-gua	D5 499

BURG-GUARD@burg.biz, www.burg-guard.com

Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

Technical specifications:

Items included in delivery

User manual

Note:

SD card is not included.

Weitere Bilder:







Recommended Accessories

SNPS-12D2	SANTEC stabilized power supply 12 V DC, 1.5 A, plug
SNCA-MK-4633	Adapter plate for SNC-231RDIA, SNC-431RDIA, SNC-241DDIA,
	SNC-831DDIA
SNCA-CMT-4852	Ceiling Mount for SANTEC IP Speed-Dome
SNCA-WM-4645	Wall bracket for IP cameras
SNCA-MK-4632	Adapter for SNC-831DDIA, Suitable for: see recommended accessories
SNCA-ICM-PFB201C	In-ceiling bracket suitable for see recommended accessories
SNCA-PM-4661	Mastadapter inkl. Spannbänder von 80 bis 130 mm
16925	Remote online support price per one hour support



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.