



BWNC-241FDIF

SANTEC 2 MP Mini IP-dome camera
2,8 mm fix lens, IR-LED, IP-66.

PRODUCT DESCRIPTION

► Application:

SANTEC SNC-241FDIF is an 3-axis dome camera with integrated IR-LEDs and it is the perfect solution for all 24/7 indoor and outdoor applications. This IP camera has a weather-proof housing (IP-66) and is vandal-proof (IK10). Thanks to 2 megapixel resolution, the images are very clear hence no detail is undetected. Due to the auto focus lens and the web interface the camera is easy to adjust. The camera comes with features such as 3DNR for noise reduction, Wide Dynamic Range (WDR), PoE and micro-SD card slot, to name but a few.

► Technical specifications:

Type	IP day/night IR dome camera
Decoding / Video / Lens	>>>>DECODING/VIDEO/LENS<<<<<
Sensor type	1/2.8" Progressive Scan Megara CMOS
Max. Picture resolution (pixel)	2 MP (1920x1080)
Video codec	H.264, H.265, MJPEG, H.264+, H.265+
Max. frame rate (fps)	25 fps at 1080p
Number of video streams	2 (1x Main, 1x Sub)
Lens mount	Intern
Iris control	DC
S/N ratio (dB)	< 50dB
Lens type	Fixlens
Focal length	2,8 mm, F2.0
Angle of view (horizontal)	106°
Angle of view (vertical)	54°
Sensitivity (Lux)	0,02lx (color)
Sensitivity (Lux)	0Lux (IR on)

BURG-GUARD GmbH
Wormgermühle, 58540 Meinerzhagen, Germany
Tel.: +49 2358 905 490, Fax: +49 2358 905 499
BURG-GUARD@burg.biz, www.burg-guard.com





► Recommended Accessories

SNPS-12D2	SANTEC stabilized power supply 12 V DC, 1.5 A, plug
SNCA-PM-4661	Mastadapter inkl. Spannbänder von 80 bis 130 mm
SNCA-MK-106	Adapter plate Please see accessory selection
SNCA-WM-4644	wall bracket for SNC-431FEIF, 211FDIA, SCC-241KDIA, SNC-231RZNA
SNCA-MK-136	Adapter / mounting kit for BURGcam DOME 303
SNCA-RD-PFA200W	Rain shade for SANTEC dome cameras