



BWNC-442RBCF

4MP IP IR Bullet camera, H.265(+), TrueWDR 120dB
RoyalNight++ - LowLight Color camera

PRODUCT DESCRIPTION

► Application:

4MP RoyalColor++ Bullet Kamera mit Weißlichtstrahler, integriertem Lautsprecher und aktiver optischer und akustischer Abschreckungsfunktion. Die Kamera kann des nachts auf bis zu 40m Entfernung farbige Bilder liefern , mit aktivem Weißlichtstrahler, erfassen. Ideal für die Nahfeld Absicherung - mit aktiver Abschreckungsfunktion durch optische und akustische Signale. Die Kamera kann auch zum Gegensprechen mit einer Person vor Ort verwendet werden. Hierfür ist die BURGcam PRO App zu empfehlen.

► Technical specifications:

Type	IP-day/night white light camera
Decoding / Video / Lens	>>>>DECODING/VIDEO/LENS<<<<<
Sensor type	1/2.7" Progressive scan CMOS
Max. Picture resolution (pixel)	4 MP (2688x1520)
Video codec	H.264, H.264+, H.265, H.265+, MJPEG(Substream)
Max. frame rate (fps)	25 fps@4MP
Number of video streams	3 (1x Main, 2x Sub)
Lens mount	Intern
Lens type	Fixlens
Focal length	2.8mm / F1.0
Angle of view (horizontal)	103°
Angle of view (vertical)	53°
Sensitivity (Lux)	0,003lx (color)
Sensitivity (Lux)	0Lux (IR on)
IR cut filter	IR-Cut filter (mechanical)
Shutter (sec.)	1/3 - 1/100,000

BURG-GUARD GmbH
Wormgermühle, 58540 Meinerzhagen, Germany
Tel.: +49 2358 905 490, Fax: +49 2358 905 499
BURG-GUARD@burg.biz, www.burg-guard.com




► Technical specifications:


MOD (minimum object distance)	0,3m
DETECT-OBSERVE-RECOGNIZ E-IDENTIFY	>DETECT-OBSERVE-RECOGNIZE-IDENTIFY<
DORI max. (Detect-Observe-Recognize-Ident ify)	63m - 25m - 13m - 6m
Features	>>>>>>>>>FEATURES<<<<<<<<<<<<<<
Day/night mode adjustment	Auto / color / B/W
Automatic gain control (AGC)	Yes
Digital noise reduction (DNR)	2NR / 3DNR
White balance	Auto / sunny / night / outdoor / manual
Backlight compensation	BLC, HLC, TrueWDR(120dB)
Wide dynamic range (WDR)	120 dB WDR (True WDR)
Digital zoom	16x, adjustable
Mirroring (vertical)	Yes
Picture flip (horizontal)	Yes
Privacy zones	Yes, 4 zones
Region of Interest (ROI)	Yes, 4 zones
Camera title	Yes
Schedule	Yes
ANR (automatic network reproduction)	Yes (for records)
Video analysis	>>>>>>>>>Videoanalytics<<<<<<<<<<<<<<
IVA via ONVIF Motion	Yes
Tripwire (IVA)	Yes
Intrusion (IVA)	Yes
Tampering Alarm	Yes
Scene change (tampering)	Yes
Audio detect (IVA)	Yes
Motion detection	Yes, 4 areas
Motion detection	AI car / human
Interface	>>>>>>>>>INTERFACE<<<<<<<<<<<<<<
Video output	Yes
Audio support	Yes
Speakers	Yes
Microphone	Built-in Mic
Audio in-/outputs	1 / 1
Audio codec	G.711a / G.711Mu / AAC / G.726
Alarm contacts I/O	1/1 -> Input: 5mA/5VDC / Output: 300mA/12VDC
Internal memory	Micro SD (optional), max. 256 GB
Network	>>>>>>>>>NETWORK<<<<<<<<<<<<<<
Ethernet connector	RJ-45
Ethernet standards	10/100Base-T
PoE standard	IEEE 802.3af

BURG-GUARD GmbH
 Wormgermühle, 58540 Meinerzhagen, Germany
 Tel.: +49 2358 905 490, Fax: +49 2358 905 499
 BURG-GUARD@burg.biz, www.burg-guard.com





Alle Angaben in mm (Zoll) - if you need technical drawings contact us
All dimensions in mm (inch) - errors and omissions excluded



► Recommended Accessories

SNPS-12D2	SANTEC stabilized power supply 12 V DC, 1.5 A, plug
SNCA-MK-4531-E	Water proof junction box for cameras IP66
SNCA-PM-4661	Mastadapter inkl. Spannbänder von 80 bis 130 mm
SNCA-CM-4670	Corner Mount Adapter for see recommended accessories
SANSWITCH-10430	4-Port ePoE Switch For transmission over 800m
BWNET-10120	1-Kanal 30W PoE Netzteil 56V 30W Gigabit Active POE injector