



BWNC-442RLNNE

SANTEC 4 MP IP box camera, 120dB True WDR, 2D/3DNR, C/S Mount, ePoE, 12VDC/24VAC, IVA

PRODUCT DESCRIPTION

► Application:

SANTEC SNC-442RLNNE is a IP camera in box design which produces excellent images at 4 megapixel resolution. This camera has manifold functions and adjustment options such as on-board video analytics, brilliant image quality thanks to 120 dB WDR (true WDR) and auto backfocus for automatic focus settings according to the lens position. Features like multi-streaming, region of interest (ROI), PoE + micro-SD card slot are of course included. SNC-442RLNNE is a camera which can be universally used, i.e. indoors as well as outdoors using a matching weather-proof housing.

► Technical specifications:

Type	IP Day/Night box camera
Decoding / Video / Lens	>>>>>DECODING/VIDEO/LENS<<<<<
Sensor type	4MP 1/1.8" LowLight CMOS
Max. Picture resolution (pixel)	4 MP (2688x1520)
Video codec	H.264, H.264+, H.265, H.265+
Streaming Method	Unicast / Multicast
Max. frame rate (fps)	25 fps@4MP
Max frame rate 1.sub stream	25 fps at D1
Max frame rate 2.sub stream	50/60fps at 1080p
Bit Rate Control	CBR / VBR
Bit Rate per channel	H.264: 24-10240Kbps ; H.265: 14-9984Kbps
Number of video streams	3 (individually adjustable)
Lens mount	DC
Lens type	C/CS mount
Focal length	-

BURG-GUARD GmbH
 Wormgermühle, 58540 Meinerzhagen, Germany
 Tel.: +49 2358 905 490, Fax: +49 2358 905 499
 BURG-GUARD@burg.biz, www.burg-guard.com



► Technical specifications:

Rel. humidity (%)	Max. 95, non-condensing
Dimensions LxWxH (mm)	135,4 x 74,4 x 65,5
Weight	0,66 Kg
Identifier	CE
Items included in delivery	Mounting accessories, RJ-45 lock
Specials	ePoE, 140dB TrueWDR, AI IVA

► Note:

The lens shown in the picture and a SD card are not included in the delivery.

► Weitere Bilder:



► Recommended Accessories

HEL-IR65D	SANTEC weather-proof housing IP-66 IR-LEDs up to 70 m
HPV42K2A700	Videotec Housing with IPM Module Camera Housing for IP-cameras
SNPS-12D2	SANTEC stabilized power supply 12 V DC, 1.5 A, plug
TR-UM06-A-IN	UniView wall and ceiling mounting box camera, indoor
TR-WM06-C-IN	Uniview wall mount for bullet camera Indoor
BWLENS-CSD037016	SANTEC 1/1.7? Tag/Nacht Objektiv 3,7-16mm
BWLENS-CSD040010	SANTEC 1/1.7? Tag/Nacht Objektiv 4-10mm
BWLENS-CSD12120	1/1.8" 12-120mm lens F1.8
SNCA-DHT-110C	Deckenhalterung für Box und Fisheye Kameras im Shop
HS-217SHB-IR	Uniview outdoor housing sunschild, IP-66
NXM36K1000	VIDEOTECH Edelstahlgehäuse, 360mm m. Sonnendach, Heizung, IN 120/230VAC, 40W
PA-KF-5.5/10	Camera Power Adapter with cable Hohlstecker Øi=2,1mm, Øa=5,5mm