



BWNC-452DBIAE

4MP Bullet,H.265(+),TrueWDR,AI DL IVA ePoE
2,7-12mm,mit (IVA+), Verpixelung

PRODUCT DESCRIPTION

► Application:

SANTEC SNC-452-E series is a 4MP bullet camera with integrated IR-LEDs and it is the perfect solution for all 24/7 indoor and outdoor applications. This IP camera has a weather-proof housing (IP-66) and is vandal-proof (IK10). Thanks to 4 megapixel resolution, the images are very clear hence no detail is undetected. Due to the auto focus lens and the web interface the camera is easy to adjust. The camera comes with features such as 3DNR for noise reduction, Wide Dynamic Range (WDR), PoE and micro-SD card slot, to name but a few.

► Technical specifications:

| | |
|---------------------------------|---|
| Type | IP Day/Night bullet AI camera |
| Decoding / Video / Lens | >>>>DECODING/VIDEO/LENS<<<<<< |
| Sensor type | 4MP 1/1.8" LowLight CMOS |
| Max. Picture resolution (pixel) | 4MP(2688x1520)/2MP(1920x1080) / 1MP(1280x720) |
| Video codec | H.264, H.265, MJPEG, H.264+, H.265+ |
| Max. frame rate (fps) | 50/60fps at 4MP |
| Number of video streams | 5 (1xMain, 4x Sub) |
| Lens mount | Intern |
| Iris control | DC |
| S/N ratio (dB) | < 50dB |
| Focal length | 2.7 - 12 mm / F1.2 |
| Lens type | 4x autofocus lens |
| Angle of view (horizontal) | 111°(W)-47°(T) |
| Angle of view (vertical) | 59°(W)?26°(T) |
| Sensitivity (Lux) | 0.001 Lux@F1.2 (color) |
| Sensitivity (Lux) | 0Lux (IR on) |

BURG-GUARD GmbH
Wormgermühle, 58540 Meinerzhagen, Germany
Tel.: +49 2358 905 490, Fax: +49 2358 905 499
BURG-GUARD@burg.biz, www.burg-guard.com



► **Technical specifications:**

| | |
|--|---|
| IR cut filter | IR-Cut filter (mechanical) |
| Shutter (sec.) | 1/3 - 1/100,000 |
| MOD (minimum object distance) | 0,6m |
| DETECT-OBSERVE-RECOGNIZ E-IDENTIFY | >DETECT-OBSERVE-RECOGNIZE-IDENTIFY< |
| DORI max. (Detect-Observe-Recognize-Ident ify) | 125m - 50m - 25m - 13m |
| DORI min. (Detect-Observe-Recognize-Ident ify) | 61m - 24m - 12m - 6m |
| Features | >>>>>>>>>FEATURES<<<<<<<<<<<<<< |
| Digital zoom | 16x, adjustable |
| Day/night mode adjustment | Auto / color / B/W |
| Automatic gain control (AGC) | Yes |
| Digital noise reduction (DNR) | 3DNR |
| White balance | Auto / sunny / night / outdoor / manual |
| Backlight compensation | BLC, HLC, TrueWDR(120dB) |
| Wide dynamic range (WDR) | 140 dB WDR (Super TrueWDR) |
| Mirroring (vertical) | Yes |
| Picture flip (horizontal) | Yes |
| Privacy zones | Yes, 4 zones |
| Region of Interest (ROI) | Yes, 4 zones |
| Defog function | Yes, digital |
| ANR (automatic network reproduction) | Yes (for records) |
| Video analysis | >>>>>>>>>Videoanalytics<<<<<<<<<<<<<< |
| IVA via ONVIF Motion | Yes |
| People counting (IVA+) | Yes |
| People in Area | Yes |
| Tripwire (IVA) | Yes |
| Intrusion (IVA) | Yes |
| Tampering Alarm | Yes |
| Scene change (tampering) | Yes |
| IVA Missing / Added | Yes |
| Audio detect (IVA) | Yes |
| Face detect (IVA) | Yes |
| Face recognition | Yes |
| face mosaic | Yes |
| people mosaic | Yes |
| Waiting time analytic | Yes |
| Motion detection | Yes, 4 areas |
| Support license plate recognize | No |
| Interface | >>>>>>>>>INTERFACE<<<<<<<<<<<<<< |

BURG-GUARD GmbH
 Wormgermühle, 58540 Meinerzhagen, Germany
 Tel.: +49 2358 905 490, Fax: +49 2358 905 499
 BURG-GUARD@burg.biz, www.burg-guard.com



► Technical specifications:

Specials face recognition

► Note:

SD card is not included.

► Weitere Bilder:



► Recommended Accessories

| | |
|------------|---|
| SNPS-12D2 | SANTEC stabilized power supply 12 V DC, 1.5 A, plug |
| BWNA-MA154 | pole mount adaptor incl. straps f. BWNC-842DBIA u. BWNC-452DBIA |
| 16925 | Remote online support price per one hour support |