BWNET-11832

8x ePoE, 8x PoE, 2x LAN, 2x SFP Switch
max. 240W, L2 managed, VLAN STP/RTSP, LACP

▪ PRODUCT DESCRIPTION

▶ Application:

The SanSwitch-24POE offer 24-Ports 10/100/1000Mbps(Gigabit) that lead you to a real gigabit connection. Users are now able to transfer high bandwidth-demanded files faster and get a real efficiency improvement with the user-friendly Web-based management interface. This product also equips 4 mini GBIC slots for your flexible fiber connection. Use of the mini-GBIC port disables the connection of its corresponding copper port automatically.

▶ Technical specifications:

Type	Switch ePoE/PoE/SFP/LAN
Number of Ethernet ports	18x RJ-45 + 2x SFP
Power over Ethernet (PoE)	Yes
Number of PoE ports	16
PoE standard	IEEE802.3at / IEEE802.3af
Max. PoE Output Voltage (port)	PoE+ up to 30 watt per port
Max. PoE power consumption	240 W
Number of gigabit ports	2 (RJ-45/SFP)
Ethernet standards	10/100Base-T(PSE/PoE), 10/100/1000Base-T RJ-45/SFP
Ethernet connector	RJ-45
SFP connector (fibre optics)	Ja, 2
Flow control	Yes IEEE 802.3x
Supported standards	IEEE 802.3ab, IEEE 802.3, IEEE 802.3u
Supported standards	IEEE 802.3z, IEEE 802.3x, IEEE 802.3az
VLAN	Yes, IEEE 802.1Q (Port & Tagged based)
Secure Mode	Downlink ports communicate only with uplink ports
QoS (quality of service)	high and low priority, WRR, 802.1P, DSCP

BURG GUARD

▶ **Technical specifications:**

LACP	Yes
Packet Buffer	2,75Mb
MAC address memory (KB)	4K
Switch capacity (GBit/s)	8.8Gbps
Forwarding Performance	5.36Mpps
Integrated web interface	Yes
Weight	3,12 kg
Voltage	100 - 240 V AC
Operating temperature (°C)	0 to +40
Rel. humidity (%)	Max. 85, non-condensing
Design	19" Rackmount
Rack mount (U)	1
Fan	Yes
Max. Power consumption (watt)	<250W
Dimensions WxDxH (mm)	440 x 300 x 44mm
Identifier	CE, FCC
Items included in delivery	Device

▶ **Recommended Accessories**

NWK-P0.55ES2	0,5m Patchcabel CAT5e, SF/UTP
NWK-P3.05ES2	3m Patchkabel CAT5e, SF/UTP