



BWPS-DC12V2A-UP

Unterputz Netzteil
12 V DC 2A, max. 24W, offenes Kabelende

PRODUCT DESCRIPTION

► Application:

SANTEC regulated DC power supply unit for integration. Grouted housing with open cable ends.

► Technical specifications:

Type	Power supply
Input voltage	110-230 VAC (50/60Hz)
Output voltage	12 V DC stabilized, max. 2 A
Capacity	12 W
Cable end	open cable ends
Classification	-
Housing colour	Black
Housing material	plastic
Operating temperature (°C)	-20 to +50
Rel. humidity (%)	Max. 95, non-condensing
Dimensions ØxH (mm)	54 x 32,5
Weight	70 g
Identifier	CE
Specials	for integration

► Note:

Einbau nur in Witterungsgeschütztem Bereich

BURG-GUARD GmbH
Wormgermühle, 58540 Meinerzhagen, Germany
Tel.: +49 2358 905 490, Fax: +49 2358 905 499
BURG-GUARD@burg.biz, www.burg-guard.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

► Recommended Accessories

HEL-IR65D

SANTEC weather-proof housing IP-66 IR-LEDs up to 70 m