



BWWC-242REIF

Thermal-Mini-Hybrid-Bulletkamera Objektiv Thermal:
3,5mm, Visuell: 4mm, IP67, ePoE, AIVA u. Feuerdetektion

PRODUCT DESCRIPTION

► Application:

The SANTEC thermal imaging cameras allow the following even in total darkness or under difficult conditions such as smoke, haze, dust and fog, to detect persons and objects. Due to AI video analysis, vehicles and persons can be detected by the SWC-241RBIF and distinguished from other objects. Thanks to real and thermal images, events can be detected early and directly verified. Due to the integrated white light emitter and loudspeaker, people can be targeted, automated, addressed and illuminated.

► Technical specifications:

Type	IP-thermal imaging camera
Decoding / Video / Lens	>>>>DECODING/VIDEO/LENS<<<<<
Sensor type real image	1/2.8" Progressive scan CMOS
Max. Picture resolution (pixel)	4 MP (2688x1520) / (2560x1440)
Thermal picture resolution (pixel)	256(H)x192(V) ; interpolated: 1280x960
Video codec	H.265(H)/H.264(B,M,H)/MJPEG
Max. frame rate (fps)	4MP@25fps
Number of video streams	2 (1x Main, 1x Sub)
Lens mount	Intern
Iris control	internal, DC
S/N ratio (dB)	< 50dB
Lens type	Fixlens
Focal length	Thermal:3,5 mm / Visual: 4mm / F1.8
Angle of view (horizontal)	Thermal: 50,6° / Visual: 80°
Angle of view (vertical)	Thermal: 37,8° / Visual: 45°
Sensitivity (Lux)	0,005lx (color)


BURG-GUARD GmbH
Wormgermühle, 58540 Meinerzhagen, Germany
Tel.: +49 2358 905 490, Fax: +49 2358 905 499
BURG-GUARD@burg.biz, www.burg-guard.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

SD card is not included.

► Weitere Bilder:



Irrtum und technische Änderung vorbehalten.

► Recommended Accessories

SNPS-12D2	SANTEC stabilized power supply 12 V DC, 1.5 A, plug
SNCA-PM-4661	Mastadapter inkl. Spannbänder von 80 bis 130 mm
16925	Remote online support price per one hour support
SNCA-MK-4531-E	Water proof junction box for cameras IP66
BWNET-10120	1-Kanal 30W PoE Netzteil 56V 30W Gigabit Active POE injector
SNCA-WM-4644	wall bracket for SNC-431FEIF, 211FDIA, SCC-241KDIA, SNC-231RZNA
SNCA-MK-106	Adapter plate Please see accessory selection

BURG-GUARD GmbH
 Wormgermühle, 58540 Meinerzhagen, Germany
 Tel.: +49 2358 905 490, Fax: +49 2358 905 499
 BURG-GUARD@burg.biz, www.burg-guard.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.