



excl. sunshield

EXHC203R

VIDEOTECH EX-geschütztes Gehäuse
230VAC, 3-fach Heizung, RAL7032

PRODUCT DESCRIPTION

► Application:

The weatherproof housing is made of the high-quality extruded aluminum was specifically designed for easy and inexpensive to install and can be opened from the side. Also this case corresponds to the Protection class IP-66. Thermostat and heating are pre-assembled.

► Technical specifications:

Type	Camera housing
Housing type	Explosion-proof housing
Classification	IP-66
Housing colour	RAL 9002 (gray white)
Sun shield	Yes
Front screen	Non-reflecting glass, hardened
Heater	Yes
Integrated IR-LEDs	No
Installation option	Wall mount (with extra bracket)
Cabling run	2 holes for cable glands 3/4" NPT
Operating temperature (°C)	-40 to +50
Storage temperature (°C)	0 to +40
Rel. humidity (%)	Max. 95, non-condensing
Outer dimensions WxHxD (mm)	210 x 210 x 427.5
Internal dimensions WxHxD (mm)	100 x 100 x 280
Max. Power consumption (watt)	82
Voltage	~24Vac or ~230Vac
Weight	15kg

BURG-GUARD GmbH
Wormgermühle, 58540 Meinerzhagen, Germany
Tel.: +49 2358 905 490, Fax: +49 2358 905 499
BURG-GUARD@burg.biz, www.burg-guard.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

► Technical specifications:

Identifier	CE, ATEX, IECEx, EAC EX, KCs
Items included in delivery	Housing excl. bracket and sunshield
Specials	ex-proof

► Note:

Sonnendach und Wandarm nicht im Lieferumfang einhalten
Empfohlener Wandarm WBLA
Zertifizierungen Ex d für den Einsatz bei Zone 1 und 2, Gruppe IIC (Gas) und Ex tb
bei Zone 21 und 22 (Pulver)

► Weitere Bilder:



excl. sunshield and bracket

► Recommended Accessories

EXHS000	Sunshield for EX-housing EXHC000
---------	----------------------------------