



HDMI-700-E

HDMI Extender
Transmission via UTP up to 60m

PRODUCT DESCRIPTION

► Application:

Übertragung von FullHD (1080p) HDMI Signalen über CAT6 Kabel bis zu 50m. Die Übertragung von IR-Signalen ins unidirektional möglich. HDMI Signal kann am Sender über den HDMI Loop Ausgang lokal verwendet werden. Verbessertes Anti-Static und Anti-Interferenz Schutz für hohe Performance.

► Technical specifications:

Type	Repeater
Input Signal	HDMI
Relay Output	HDMI
Transmission mode	Twisted-pair (RJ-45)
max. linkdistance	50 m (CAT 6, DC Impedanz < 9.5Ohm/100m)
HDCP Version	Support HDCP 1.2
HDMI Version	Support 1.3 and lower versions
More resolutions	1080p / 1080i / 720p / 720i / 576p / 576i / 480p
Voltage	5 V DC
Max. Power consumption (watt)	3W
Housing material	Aluminium
Housing colour	Black
Dimensions WxHxD (mm)	79.5mmx68mmx16.5mm
Weight	133g
Operating temperature (°C)	-10 - 55°C
Rel. humidity (%)	Max. 95, non-condensing
Items included in delivery	1x Transmitter, 1x Receiver, 1x power supply
Specials	Transmission HDMI signal via UTP cabel

BURG-GUARD GmbH
Wormgermühle, 58540 Meinerzhagen, Germany
Tel.: +49 2358 905 490, Fax: +49 2358 905 499
BURG-GUARD@burg.biz, www.burg-guard.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

► Technical specifications:

MTBF

>5000h

► Weitere Bilder:



BURG-GUARD GmbH
Wormgermühle, 58540 Meinerzhagen, Germany
Tel.: +49 2358 905 490, Fax: +49 2358 905 499
BURG-GUARD@burg.biz, www.burg-guard.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.