



## HEL-IR65D

SANTEC weather-proof housing IP-66  
IR-LEDs up to 70 m

### PRODUCT DESCRIPTION

#### ► Application:

This is a very specific weather-proof housing (IP-66) with integrated IR-LEDs with up to 70 m range. A wall bracket with integrated cable management is included in the delivery. It is simple to install a SANTEC day/night camera because the housing can easily be opened.

#### ► Technical specifications:

Type	IR-Weather proof housing
Housing type	IR-Weather proof housing
Classification	IP-66
Housing material	Aluminium
Housing colour	Gray
Sun shield	Yes
Front screen	Non-reflecting glass, hardened
Heater	Yes
Thermostat	Yes
Fan	Yes
Integrated IR-LEDs	Yes
IR wave length	850
IR range (m)	up to 70
IR illumination angle (horizontal)	30 °
IR switch contact	Yes
Twilight switch	Yes, adjustable
Switch contact	Yes
Installation option	Wall mounting

BURG-GUARD GmbH  
Wormgermühle, 58540 Meinerzhagen, Germany  
Tel.: +49 2358 905 490, Fax: +49 2358 905 499  
BURG-GUARD@burg.biz, www.burg-guard.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

### ► Technical specifications:

Cable management	Yes
Cabling run	Yes, intern
Integrated wall bracket	Yes
Operating temperature (°C)	-20 to +60
Outer dimensions WxHxD (mm)	150 x 160 x 374
Internal dimensions WxHxD (mm)	90 x 65 x 180
Voltage	230 V AC
Max. Power consumption (watt)	32

### ► Note:

Please note: If lenses with a focal length of < 4 mm are used, a "tunnel vision" may occur, i.e. parts of the housing are visible. The range of the built-in IR-LEDs strongly depend on the location and the surroundings. Strongly absorbent surfaces, e.g. dark, rough structures (floor, lawn or asphalt), may lead to a considerable reduction of the maximum range.

### ► Weitere Bilder:



### ► Recommended Accessories

HEL-IRMAST	Pole mount/corner adapter for HEL-62D/-IR65D/-IR75D housing
KS-EXT-1	Extension cable for camera set per meter
15001	Lens mounting charge for AI lenses, video, manual zoom
BWNC-442RLNNE	SANTEC 4 MP IP box camera, 120dB True WDR, 2D/3DNR, C/S Mount, ePoE, 12VDC/24VAC, IVA
SCC-341KLNN	SANTEC HD-CVI(1080P)/CVBS(960H)/SDI box camera C/CS Mount, 12 V DC / 24 V AC
BWPS-DC12V2A-UP	Unterputz Netzteil 12 V DC 2A, max. 24W, offenes Kabelende