



HOT39D2A000

Videotec weatherproof housing with Heating (24 V AC), plastic

PRODUCT DESCRIPTION

► Application:

This new Videotec weatherproof housing is constructed of heavy plastic, to the camera installed at the side hinged and fitted with a glass front window. The bright housing color adjusts to any installation environment is good. The installation the camera is simply the easily accessible camera sled.

► Technical specifications:

Type	Camera housing
Housing type	Weather chassis
Classification	IP-67
Housing material	High-Technopolymer (Polycarbonat)
Housing colour	RAL 9002 (gray white)
Sun shield	No
Front screen	Non-reflecting glass, hardened
Heater	Yes
Thermostat	Yes
Fan	No
Cooling	No
Integrated IR-LEDs	No
Twilight switch	No
Switch contact	No
Wiper	No
Installation option	Wall mounting
Cable management	No
Cabling run	Yes, 2x PG

BURG-GUARD GmbH
Wormgermühle, 58540 Meinerzhagen, Germany
Tel.: +49 2358 905 490, Fax: +49 2358 905 499
BURG-GUARD@burg.biz, www.burg-guard.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

► Technical specifications:

Integrated wall bracket	No
Integrated power supply (optional)	Yes, 12V DC
Operating temperature (°C)	-20 to +60
Outer dimensions WxHxD (mm)	146 x 128 x 391
Internal dimensions WxHxD (mm)	70 x 70 x 250
Voltage	12 V DC / 24 V AC

► Note:

Please note: If lenses with a focal length of < 4 mm are used, a "tunnel vision" may occur, i.e. parts of the housing are visible.

► Recommended Accessories

WBJA	SANTEC bracket for protective housing of the HEL-Series, Colour: cream white (RAL9002)
WBOVA2	Bracket with integrated cable management HPV42K for housing, protection class IP 54