



HPV42K1A000

Protective housing with sunshield
+ Heating, 230 VAC, 270mm, (IP-66), RAL-9002

PRODUCT DESCRIPTION

► Application:

The HPV42K1A000 housing is made of most resistant techopolymer material in white creamy color. The installation is very convenient due to the side opening of the housing. This housing is also weatherproof with standard IP66. The power connection should be 230 V AC.

► Technical specifications:

Type	Camera housing
Housing type	Weather chassis
Classification	IP-66
Housing material	High-Technopolymer (Polycarbonat)
Housing colour	RAL 9002 (gray white)
Sun shield	Yes
Front screen	Non-reflecting glass, hardened
Heater	Yes
Thermostat	Yes
Fan	No
Cooling	No
Integrated IR-LEDs	No
Switch contact	No
Wiper	No
Installation option	Wall mounting
Cable management	No
Cabling run	Yes, 2x PG
Integrated wall bracket	No

BURG-GUARD GmbH
Wormgermühle, 58540 Meinerzhagen, Germany
Tel.: +49 2358 905 490, Fax: +49 2358 905 499
BURG-GUARD@burg.biz, www.burg-guard.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

► Technical specifications:

Integrated power supply (optional)	No
Operating temperature (°C)	-20 to +60
Storage temperature (°C)	-20 to +60
Outer dimensions WxHxD (mm)	156 x 115 x 466
Internal dimensions WxHxD (mm)	70 x 70 x 270
Voltage	100 - 240 V AC

► Note:

Please note: If lenses with a focal length of < 4 mm are used, a "tunnel vision" may occur, i.e. parts of the housing are visible.

► Recommended Accessories

WBOVA2	Bracket with integrated cable management HPV42K for housing, protection class IP 54
WBJA	SANTEC bracket for protective housing of the HEL-Series, Colour: cream white (RAL9002)
WBOVA2-IP66/A	Bracket with integrated cable management HPV42K for housing, protection class IP 66, OWBIP3