



## HPV42K2A700

Videotec Housing with IPM Module  
Camera Housing for IP-cameras

### PRODUCT DESCRIPTION

#### ► Application:

The HPV42K2A700 housing is made of most resistant technopolymer material in white creamy color. The installation is very convenient due to the side opening of the housing. This housing is also weatherproof with standard IP66. An IPM-Module is installed to give operating voltage to PoE IP cameras and GEKO IRH Illuminators.

#### ► Technical specifications:

Type	Camera housing
Housing type	Weather chassis
Classification	IP-66
Housing material	High-Technopolymer (Polycarbonat)
Housing colour	RAL 9002 (gray white)
Sun shield	Yes
Front screen	Clear glass, hardened
Heater	Yes
Thermostat	Yes
Fan	Yes
Cooling	No
Integrated IR-LEDs	No
Switch contact	No
Wiper	No
Installation option	Wall mounting
Cable management	No
Cabling run	Yes, 2x PG

BURG-GUARD GmbH  
Wormgermühle, 58540 Meinerzhagen, Germany  
Tel.: +49 2358 905 490, Fax: +49 2358 905 499  
BURG-GUARD@burg.biz, www.burg-guard.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

### ► Technical specifications:

Integrated wall bracket	No
Integrated power supply (optional)	No
Operating temperature (°C)	-30 to +60
Outer dimensions WxHxD (mm)	156 x 115 x 466
Internal dimensions WxHxD (mm)	70 x 70 x 230
Voltage	IEEE 802.3af, IEEE 802.3at/PoE Plus
Weight	1.6 kg
Identifier	CE
Specials	built-in IPM-Module

### ► Note:

Please note: If lenses with a focal length of < 4 mm are used, a "tunnel vision" may occur, i.e. parts of the housing are visible.

### ► Weitere Bilder:



### ► Recommended Accessories

WBOVA2	Bracket with integrated cable management HPV42K for housing, protection class IP 54
WBOVA2-IP66	Bracket with integrated cable management HPV42K for housing, protection class IP 66, OWBIP2
OWBIP3	Rubber ring 1xM12, 1xM16, 1xM20 for WBOV