



HS-217SHB-IR

Uniview outdoor housing
sunshild, IP-66

PRODUCT DESCRIPTION

► Application:

This is a very specific weather-proof housing (IP-66) with integrated IR-LEDs with up to 100 m range. It is simple to install a Uniview day/night camera because the housing can easily be opened.

► Technical specifications:

Type	IR-Weather proof housing
Housing type	IR-Weather proof housing
Classification	IP-66
Housing material	Aluminium
Housing colour	White
Sun shield	Yes
Front screen	Front glass
Heater	Yes, 10Watt
Thermostat	Yes
Fan	Yes, 1,8Watt
Integrated IR-LEDs	Yes, 18 Watt
IR wave length	850
IR range (m)	up to 100
Installation option	Wall mounting
Operating temperature (°C)	-40 to +60
Outer dimensions LxBxH (mm)	462 x 161 x 112
Internal dimensions LxBxH (mm)	300 x 105 x 78,5
Voltage	24 V AC
Max. Power consumption (watt)	29,8

BURG-GUARD GmbH
Wormgermühle, 58540 Meinerzhagen, Germany
Tel.: +49 2358 905 490, Fax: +49 2358 905 499
BURG-GUARD@burg.biz, www.burg-guard.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

Note:

The range of the built-in IR-LEDs strongly depend on the location and the surroundings. Strongly absorbent surfaces, e.g. dark, rough structures (floor, lawn or asphalt), may lead to a considerable reduction of the maximum range.

► Weitere Bilder:



► Recommended Accessories

TR-CM06-IN

Uniview Ceiling mounting suitable for: IPC54X u. IPC56X Serie

IPC562E-DUG

Uniview 2 MP 120dB,WDR,HLC, IP-Boxkamera Lowlight mit optischer defog-Funktion