



IPC2124LE-ADF28KM-G

4MP HD Mini IR bullet IP camera, 2.8mm fix lens
2,8 mm Festobjektiv, IP67, 120dB WDR

PRODUCT DESCRIPTION

► Application:

Uniview IP indoor/outdoor camera IPC2124SR3-DPF36 with integrated IR-LEDs is the perfect solution for all 24/7 indoor/outdoor applications. Thanks to its 4 mega pixel resolution and the integrated IR-LEDs, the camera delivers detailed and brilliant pictures in real-time at all times. The slim camera design and the comprehensive set of accessories enable installations almost everywhere.

► Technical specifications:

Type	IP Day/Night IR bullet camera
Decoding / Video / Lens	>>>>>DECODING/VIDEO/LENS<<<<<<
Sensor type	1/3" Progressive Scan CMOS
Max. Picture resolution (pixel)	4MP (2592×1520), 4MP (2560×1440), 3MP (2048×1520)
Video codec	(U-)H.265,(U-) H.264, MJPEG
Streaming Method	Unicast / Multicast
Max. frame rate (fps)	20/25 fps at 4MP, 30 fps at 3MP
Bit Rate Control	CBR / VBR
Bit Rate per channel	H.265/H.265: 128-16384Kbps
Number of video streams	3 (individually adjustable)
Lens mount	Intern
Lens type	Fix lens
Focal length	2,8mm
Aperture (max)	F1.6
Optical zoom	-
Digital zoom	Yes
Angle of view (horizontal)	101.1°

BURG-GUARD GmbH
Wormgermühle, 58540 Meinerzhagen, Germany
Tel.: +49 2358 905 490, Fax: +49 2358 905 499
BURG-GUARD@burg.biz, www.burg-guard.com



► **Technical specifications:**

Angle of view (vertical)	55.3°
MOD (minimum object distance)	0,5m
Pan/Tilt/Rotation Range	Pan: 0°-360° ;Tilt:0°-90° ;Ratation:0°-360°
Sensitivity (Lux)	Colour: 0,002
Sensitivity (Lux)	0 (IR on)
S/N ratio (dB)	>56dB
IR cut filter	ICR
Features	>>>>>>>>>FEATURES<<<<<<<<<<<<<<
Day/night mode adjustment	Auto / color / B/W
Automatic gain control (AGC)	Yes
Digital noise reduction (DNR)	2NR / 3DNR
Shutter (sec.)	1/6 - 1/100000
White balance	Auto, manually and others
Backlight compensation	120 dB True WDR, BLC, HLC
Wide dynamic range (WDR)	120 dB WDR (True WDR)
Watermark	Yes
Defog function	Yes, digital
Electronic Image Stabilization (EIS)	No
Mirroring (vertical)	Yes
Picture flip (horizontal)	Yes
Camera title	Yes
Video output	No
Privacy zones	Yes, 8
Region of Interest (ROI)	Yes, 8 zones
Video analysis	>>>>>>>>>Videoanalytics<<<<<<<<<<<<<<
Motion detection	Yes, 4 areas
Tampering Alarm	Yes
Scene change (tampering)	Yes
IVA via ONVIF Motion	No
Interface	>>>>>>>>>INTERFACE<<<<<<<<<<<<<<
Audio in-/outputs	-
Audio codec	-
Alarm contacts I/O	No
Switch output contacts	No
Switch input contacts	No
SD-card slot	Yes, max. 256GB (optional)
Network	>>>>>>>>>NETWORK<<<<<<<<<<<<<<
Ethernet connector	RJ-45
Ethernet standards	10Base-TX/100Base-TX
Ethernet speed	10 / 100 Mbit
PoE standard	IEEE 802.3af
ePoE / Long-Range-PoE	No
Remote	>>>>>>>>>REMOTE<<<<<<<<<<<<<<

BURG-GUARD GmbH
Wormgermühle, 58540 Meinerzhagen, Germany
Tel.: +49 2358 905 490, Fax: +49 2358 905 499
BURG-GUARD@burg.biz, www.burg-guard.com



► Technical specifications:

Max number of users	32
Alarm management	HTTP, FTP, ONVIF
Schedule	Yes
Management software support	Many VMS
Supported browser	Internet Explorer 11, Chrome, Firefox, and more
P2P support	Yes (EZCloud)
Cloud service	Yes, EZCloud UNV
Smartphone App	EZView
Push-Notification	Yes, via mobile app.
Security features	HTTPS, SSL, IP Filter
Supported protocols	HTTP,HTTPS,FTP,TCP,UDP, DHCP, SSH,NTP,ONVIF...
Supported software standards	ONVIF, API
ONVIF version/profile	ONVIF Profile S&G&T
Edge Recording	Local on desktop, FTP
General	>>>>>>>>>GENERAL<<<<<<<<<<<<
Classification	IP-67
Installation	Wall and ceiling mount
Camera mounting	Screw mounting
Housing colour	White
Housing material	Metal
Integrated IR-LEDs	Yes
Wavelength LED	850 nm
IR distance (m. ca.)	50m
Smart IR	Yes
DORI max.	63m - 25m - 13m - 6m
(Detect-Observe-Recognize-Identify)	
Voltage	12 VDC (+/-25%), PoE
Max. Power consumption (watt)	6
Operating temperature (°C)	-30 to +60
Storage temperature (°C)	0 to +50
Rel. humidity (%)	Max. 95, non-condensing
Dimensions LxWxH (mm)	190x73x71mm
Weight	0,45 Kg
Items included in delivery	Mounting accessories, RJ-45 lock

► Note:

Uniview Software, z.B. um die Geräte im Netzwerk zu suchen, finden Sie unter Software bzw. Downloads&Software.

► Weitere Bilder:

BURG-GUARD GmbH
Wormgermühle, 58540 Meinerzhagen, Germany
Tel.: +49 2358 905 490, Fax: +49 2358 905 499
BURG-GUARD@burg.biz, www.burg-guard.com





► Recommended Accessories

TR-UP06-B-IN

Uniview pole mount adapter suitable for IPC22X- u. IPC24X Serie, Outdoor

TR-A01-IN

Uniview plastic Waterproof joint TR-UP06-A-IN,TRJB07-IN,TR-JB07-A-IN