



### IPC2128SB-ADF28KMC-I

Uniview 8 MP 4K IP-IR-Bulletkamera  
2.8mm Fixobjektiv, IP67, 120dB WDR

## PRODUCT DESCRIPTION

### ► Application:

Uniview IP indoor/outdoor camera IPC2328SBR5-DPZ with integrated IR-LEDs is the perfect solution for all 24/7 indoor/outdoor applications. Thanks to its 8 mega pixel resolution and the integrated IR-LEDs, the camera delivers detailed and brilliant pictures in real-time at all times. The integrated DC 5x autofocus lens with 2,8-12mm can be controlled by the webinterface. The slim camera design and the comprehensive set of accessories enable installations almost everywhere.

### ► Technical specifications:

Type	IP Day/Night IR bullet camera
Decoding / Video / Lens	>>>>DECODING/VIDEO/LENS<<<<<<
Sensor type	1/2.7" Progressive scan CMOS
Max. Picture resolution (pixel)	8 MP (3840x2160), 5MP(2592*1944), 4MP(2560*1440)
Video codec	(U-)H.265,(U-) H.264, MJPEG
Streaming Method	Unicast / Multicast
Max. frame rate (fps)	20fps@8MP
Max frame rate 1.sub stream	30 fps at 2MP
Max frame rate 2.sub stream	30 fps at D1
Bit Rate Control	CBR / VBR
Bit Rate per channel	H.265/H.265: 128-16384Kbps
Number of video streams	3 (individually adjustable)
Lens mount	Intern
Lens type	Fix lens
Focal length	2,8mm
Aperture (max)	F2.0

BURG-GUARD GmbH  
Wormgermühle, 58540 Meinerzhagen, Germany  
Tel.: +49 2358 905 490, Fax: +49 2358 905 499  
BURG-GUARD@burg.biz, www.burg-guard.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.





### Weitere Bilder:



### ► Recommended Accessories

TR-UP06-B-IN

Uniview pole mount adapter suitable for IPC22X- u. IPC24X Serie, Outdoor

TR-JB07-D-IN

Uniview IN-/Outdoor Junction Box f. IPC22X- u. IPC74X Serie

TR-A01-IN

Uniview plastic Waterproof joint TR-UP06-A-IN,TRJB07-IN,TR-JB07-A-IN