



IPC3235ER3-DUVZ

SANTEC 5 MP WDR IP-IR dome camera
2.7-13.5 mm mot.lens, IP67, IK10

PRODUCT DESCRIPTION

► Application:

Uniview IP indoor/outdoor camera IPC3235ER3-DUVZ with integrated IR-LEDs is the perfect solution for all 24/7 indoor/outdoor applications. Thanks to its 5 mega pixel resolution and the integrated IR-LEDs, the camera delivers detailed and brilliant pictures in real-time at all times. The integrated DC 5x autofocus lens with 2,7-13,5mm can be controlled by the webinterface. The slim camera design and the comprehensive set of accessories enable installations almost everywhere.

► Technical specifications:

Type	IP day/night IR dome camera
Decoding / Video / Lens	>>>>DECODING/VIDEO/LENS<<<<<<
Sensor type	1/2.7" Progressive scan CMOS
Starlight	Yes
Max. Picture resolution (pixel)	5 MP (2592x1944)
Video codec	(U-)H.265,(U-) H.264, MJPEG
Streaming Method	Unicast / Multicast
Max. frame rate (fps)	20 fps at 5MP, 30 fps at 4MP
Max frame rate 1.sub stream	30 fps at 2MP
Max frame rate 2.sub stream	30 fps at D1
Bit Rate Control	CBR / VBR
Bit Rate per channel	H.265/H.265: 128-16384Kbps
Number of video streams	3 (individually adjustable)
Lens mount	Intern
Lens type	Built-in motorized lens
Focal length	2,7 - 13,5 mm

BURG-GUARD GmbH
Wormgermühle, 58540 Meinerzhagen, Germany
Tel.: +49 2358 905 490, Fax: +49 2358 905 499
BURG-GUARD@burg.biz, www.burg-guard.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

► Technical specifications:

DORI max. (Detect-Observe-Recognize-Identify)	304m - 122m - 61m - 30m
DORI min. (Detect-Observe-Recognize-Identify)	61m - 24m - 12m - 6m
Voltage	12 VDC (+/-25%), PoE
Max. Power consumption (watt)	8,7
Operating temperature (°C)	-35 to +60
Rel. humidity (%)	Max. 95, non-condensing
Dimensions ØxH (mm)	148 x 111,3
Weight	0,75 Kg
Items included in delivery	Mounting accessories, RJ-45 lock

► Note:

Uniview Software, z.B. um die Geräte im Netzwerk zu suchen, finden Sie unter Software bzw. Downloads&Software.

► Weitere Bilder:



► Recommended Accessories

TR-WM04-IN	Uniview Wall mounting indoor f. IPC323X Serie
TR-SM04-IN	Uniview adaptor plate indoor, suitable for IPC323 dome series
TR-UF45-E-IN	Uniview Fixed Dome adaptor plate, Indoor, Ceiling and wall mounting
TR-JB04-C-IN	Uniview Dome junction box Wall installation