



IPC3238SB-ADZK-I0

8MP HD Intelligent LighterHunter IR IP VF Dome
2.8-12mm, IR, 120dB TrueWDR, HLC, BLC

PRODUCT DESCRIPTION

► Application:

IPC3238SB-ADZK-I0 8MP HD Intelligent LighterHunter IR VF Dome Network Camera ? High quality image with 8MP, 1/2.8"CMOS sensor ? 8MP (3840*2160)@20fps; 5MP (3072*1728)@30/25fps; 4MP (2560*1440)@30/25fps; 2MP (1920*1080) @30/25fps ? Ultra 265, H.265, H.264, MJPEG ? LightHunter technology ensures ultra-high image quality in low illumination environment ? 120dB true WDR technology enables clear image in strong light scene ? Support 9:16 Corridor Mode ? Built-in Mic ? Alarm:1 in/1 out, Audio: 1 in/1 out ? Smart IR, up to 40m (131ft) IR distance ? Supports 256 G Micro SD card ? IK10 vandal resistant ? IP67 protection ? Support PoE power supply

► Technical specifications:

Type	IP day/night IR dome camera
Decoding / Video / Lens	>>>>>DECODING/VIDEO/LENS<<<<<<
Sensor type	1/2.8" Progressive scan CMOS
LightHunter	Yes
Max. Picture resolution (pixel)	8 MP (3840x2160), 5MP(2592*1944), 4MP(2560*1440)
Video codec	(U-)H.265,(U-) H.264, MJPEG
Streaming Method	Unicast / Multicast
Max. frame rate (fps)	20fps@8MP
Max frame rate 1.sub stream	30 fps at 2MP
Max frame rate 2.sub stream	30 fps at D1
Bit Rate Control	CBR / VBR
Number of video streams	3 (individually adjustable)
Lens mount	Intern
Lens type	Built-in motorized lens

BURG-GUARD GmbH
Wormgermühle, 58540 Meinerzhagen, Germany
Tel.: +49 2358 905 490, Fax: +49 2358 905 499
BURG-GUARD@burg.biz, www.burg-guard.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

Note:

Uniview Software, z.B. um die Geräte im Netzwerk zu suchen, finden Sie unter Software bzw. Downloads&Software.

► Weitere Bilder:



► Recommended Accessories

TR-FM152-A-IN	Uniview fixed Dome, in ceiling mounting Indoor, f. IPC323X Series
TR-WM04-IN	Uniview Wall mounting indoor f. IPC323X Serie
TR-UP06-B-IN	Uniview pole mount adapter suitable for IPC22X- u. IPC24X Serie, Outdoor
TR-SM04-IN	Uniview adaptor plate indoor, suitable for IPC323 dome series
TR-A01-IN	Uniview plastic Waterproof joint TR-UP06-A-IN,TRJB07-IN,TR-JB07-A-IN
TR-JB04-C-IN	Uniview Dome junction box Wall installation