



## IPC562E-DUG

Uniview 2 MP 120dB,WDR,HLC, IP-Boxkamera  
Lowlight mit optischer defog-Funktion

### PRODUCT DESCRIPTION

#### ► Application:

Uniview IP indoor camera IPC562E-DUG is the perfect solution for all 24/7 indoor applications. Thanks to its 2 mega pixel resolution the camera delivers detailed and brilliant pictures in real-time at all times. The slim camera design and the comprehensive set of accessories enable installations almost everywhere.

#### ► Technical specifications:

|                                 |                              |
|---------------------------------|------------------------------|
| Type                            | IP Day/Night box camera      |
| Decoding / Video / Lens         | -----                        |
| Sensor type                     | 1/1,9" Progressive Scan CMOS |
| Max. Picture resolution (pixel) | 2 MP (1920x1080)             |
| Video codec                     | (U-)H.265,(U-) H.264, MJPEG  |
| Streaming Method                | Unicast / Multicast          |
| Max. frame rate (fps)           | 60 at 2 MP (1920x1080)       |
| Max frame rate 1.sub stream     | 60 fps at 2MP                |
| Max frame rate 2.sub stream     | 60 fps at D1                 |
| Bit Rate Control                | CBR / VBR                    |
| Bit Rate per channel            | H.265/H.265: 128-16384Kbps   |
| Number of video streams         | 3 (individually adjustable)  |
| Lens mount                      | DC                           |
| Lens type                       | C/CS mount                   |
| Optical zoom                    | -                            |
| Digital zoom                    | -                            |
| Sensitivity (Lux)               | Colour: 0,0005               |
| Sensitivity (Lux)               | 0,0005 (IR on)               |

BURG-GUARD GmbH  
Wormgermühle, 58540 Meinerzhagen, Germany  
Tel.: +49 2358 905 490, Fax: +49 2358 905 499  
BURG-GUARD@burg.biz, www.burg-guard.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

► **Technical specifications:**

|                                      |                                                  |
|--------------------------------------|--------------------------------------------------|
| S/N ratio (dB)                       | >52dB                                            |
| IR cut filter                        | ICR                                              |
| Shutter (sec.)                       | 1/6 - 1/100000                                   |
| Pan/Tilt/Rotation Range              | -                                                |
| Features                             | -----                                            |
| Day/night mode adjustment            | Auto / color / B/W                               |
| Automatic gain control (AGC)         | Yes                                              |
| Digital noise reduction (DNR)        | 2NR / 3DNR                                       |
| White balance                        | Auto, manually and others                        |
| Backlight compensation               | 120 dB True WDR, BLC, HLC                        |
| Wide dynamic range (WDR)             | 120 dB WDR (True WDR)                            |
| Watermark                            | Yes                                              |
| Defog function                       | Yes, optical and digital                         |
| Electronic Image Stabilization (EIS) | No                                               |
| Mirroring (vertical)                 | Yes                                              |
| Picture flip (horizontal)            | Yes                                              |
| Camera title                         | Yes                                              |
| Corridor mode                        | Yes, 9:16                                        |
| Privacy zones                        | Yes, 8                                           |
| Region of Interest (ROI)             | Yes, 8 zones                                     |
| Motion detection                     | Yes, 4 areas                                     |
| Tampering Alarm                      | Yes                                              |
| Scene change (tampering)             | Yes                                              |
| IVA via ONVIF Motion                 | No                                               |
| People counting (IVA+)               | Yes                                              |
| Heatmap (IVA+)                       | No                                               |
| Tripwire (IVA)                       | Yes                                              |
| Intrusion (IVA)                      | Yes                                              |
| Object Apear and disappear (IVA)     | No                                               |
| Fast-Moving (IVA)                    | No                                               |
| Crowd Gathering Estimation           | No                                               |
| Loitering detection (IVA)            | No                                               |
| Face detect (IVA)                    | Yes                                              |
| Audio detect (IVA)                   | Yes                                              |
| Alarm management                     | HTTP, FTP, ONVIF                                 |
| Schedule                             | Yes                                              |
| Edge Recording                       | Local on desktop, FTP                            |
| ANR (automatic network reproduction) | Yes (for records)                                |
| Interface                            | -----                                            |
| Video output                         | BNC, 75 Ohm 1 Vpp                                |
| Audio in-/outputs                    | 1x Input: 35 kOhm/2Vpp ; 1x Output: 600 Ohm/2Vpp |
| Audio codec                          | G.711a / G711u                                   |

BURG-GUARD GmbH  
 Wormgermühle, 58540 Meinerzhagen, Germany  
 Tel.: +49 2358 905 490, Fax: +49 2358 905 499  
 BURG-GUARD@burg.biz, www.burg-guard.com



► **Technical specifications:**

|                               |                                                  |
|-------------------------------|--------------------------------------------------|
| Audio sampling rate           | 8 KHz                                            |
| Alarm contacts I/O            | 2 / 1                                            |
| Switch output contacts        | 1                                                |
| Switch input contacts         | 2                                                |
| Control interface             | RS-485                                           |
| Relay type (output)           | FET (Open Source)                                |
| Max. switching voltage        | 12VDC/0,1A                                       |
| Max. switching power          | 1,2W                                             |
| SD-card slot                  | Yes, micro SD card up to 128GB                   |
| ABF (auto back focus)         | Yes                                              |
| Network                       | -----                                            |
| Ethernet connector            | RJ-45 + SFP                                      |
| Ethernet standards            | 100/1000Base-TX (RJ-45) / 100/1000 FX (SFP)      |
| Ethernet speed                | 10 / 100 / 1000 Mbit (Gigabit)                   |
| PoE standard                  | IEEE 802.3af                                     |
| SFP connector (fibre optics)  | Yes                                              |
| ePoE / Long-Range-PoE         | Ja, bis 250m (with UNV- recorder or -IP-Switch ) |
| Remote                        | -----                                            |
| Max number of users           | 32                                               |
| Management software support   | Many VMS                                         |
| Supported browser             | Internet Explorer 11                             |
| P2P support                   | Yes (EZCloud)                                    |
| Cloud service                 | Yes, EZCloud UNV                                 |
| Smartphone App                | EZView                                           |
| Push-Notification             | Yes, via mobile app.                             |
| Security features             | HTTPS, SSL, IP Filter                            |
| Supported protocols           | HTTP,HTTPS,FTP,TCP,UDP, DHCP, SSH,NTP,ONVIF...   |
| Supported software standards  | ONVIF, API                                       |
| ONVIF version/profile         | Profile S, Profile G                             |
| General                       | -----                                            |
| Classification                | -                                                |
| Vandal-proof                  | -                                                |
| Installation                  | Wall and ceiling mount                           |
| Camera mounting               | Screw mounting                                   |
| Housing colour                | White / black                                    |
| Housing material              | Metal                                            |
| Integrated IR-LEDs            | No                                               |
| Wavelength LED                | -                                                |
| Voltage                       | 24VAC , 12VDC (+/- 25%), PoE                     |
| Max. Power consumption (watt) | 6,8                                              |
| Operating temperature (°C)    | -20 to +60                                       |
| Rel. humidity (%)             | Max. 90, non-condensing                          |
| Dimensions LxWxH (mm)         | 151,5 x 71x 65                                   |
| Weight                        | 0,48 Kg                                          |

BURG-GUARD GmbH  
 Wormgermühle, 58540 Meinerzhagen, Germany  
 Tel.: +49 2358 905 490, Fax: +49 2358 905 499  
 BURG-GUARD@burg.biz, www.burg-guard.com



### ► Technical specifications:

Items included in delivery                      Mounting accessories, RJ-45 lock

### ► Note:

Uniview Software, z.B. um die Geräte im Netzwerk zu suchen, finden Sie unter Software bzw. Downloads&Software.

### ► Weitere Bilder:



### ► Recommended Accessories

|              |                                                      |
|--------------|------------------------------------------------------|
| TR-UM06-A-IN | UniView wall and ceiling mounting box camera, indoor |
| HS-217SHB-IR | Uniview outdoor housing sunshield, IP-66             |
| TR-WM06-C-IN | Uniview wall mount for bullet camera Indoor          |