



## IPC6322SR-X22P-C

SANTEC 2 MP IP-Speed Dome  
22x opti.Zoom 5.2-114.4mm,IP66

### PRODUCT DESCRIPTION

#### ► Application:

Uniview IP outdoor camera IPC6322SR-X22P-C with integrated IR-LEDs is the perfect solution for all 24/7 outdoor applications. Thanks to its 2 mega pixel (1080p) resolution and the integrated IR-LEDs, the camera delivers detailed and brilliant pictures in real-time at all times. The integrated DC 22x autofocus lens with 5,2-114,4mm can be controlled by the webinterface. The slim camera design and the comprehensive set of accessories enable installations almost everywhere.

#### ► Technical specifications:

Type	IP day/night IR speed dome
Decoding / Video / Lens	-----
Sensor type	1/2.9" Progressive Scan CMOS
Max. Picture resolution (pixel)	2 MP (1920x1080)
Video codec	(U-)H.265,(U-) H.264, MJPEG
Streaming Method	Unicast / Multicast
Max. frame rate (fps)	30 at 2 MP (1920x1080)
Max frame rate 1.sub stream	30 fps at 2MP
Max frame rate 2.sub stream	30 fps at D1
Bit Rate Control	CBR / VBR
Bit Rate per channel	H.265/H.265: 128-16384Kbps
Number of video streams	3 (individually adjustable)
Lens mount	Intern
Lens type	Built-in motorized lens
Focal length	5,2 mm - 114,4 mm
Aperture (max)	F1.5

BURG-GUARD GmbH  
Wormgermühle, 58540 Meinerzhagen, Germany  
Tel.: +49 2358 905 490, Fax: +49 2358 905 499  
BURG-GUARD@burg.biz, www.burg-guard.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

► **Technical specifications:**

Optical zoom	22x, adjustable
Angle of view (horizontal)	54,40° - 3,44°
Sensitivity (Lux)	Colour: 0,01
Sensitivity (Lux)	0 (IR on)
S/N ratio (dB)	>55dB
IR cut filter	ICR
Shutter (sec.)	1/6 - 1/100000
Pan/Tilt/Rotation Range	Pan: 0°-360° ; Tilt: -15°-90° ; Rotation: 0°-360°
Tilt speed	0,1° to 80° /s
Rotation speed	0,1° bis 240°/s.
Preset speed	Pan: 300°/s, Tilt: 80°/s
Preset positions	1024
Tours	Yes
Pattern	Yes
Features	-----
Day/night mode adjustment	Auto / color / B/W
Automatic gain control (AGC)	Yes
Digital noise reduction (DNR)	2NR / 3DNR
White balance	Auto, manually and others
Backlight compensation	BLC, HLC, DWDR
Wide dynamic range (WDR)	DWDR
Watermark	Yes
Defog function	Yes, digital
Electronic Image Stabilization (EIS)	Yes
Mirroring (vertical)	Yes
Picture flip (horizontal)	Yes
Camera title	Yes
Video output	No
Corridor mode	No
Privacy zones	Yes, 24
Region of Interest (ROI)	Yes, 8 zones
Motion detection	Yes, 4 areas
Tampering Alarm	Yes
Scene change (tampering)	No
IVA via ONVIF Motion	No
People counting (IVA+)	Yes
Heatmap (IVA+)	No
Tripwire (IVA)	Yes
Intrusion (IVA)	Yes
Object Apear and disappear (IVA)	No
Fast-Moving (IVA)	No
Crowd Gathering Estimation	No
Loitering detection (IVA)	No

BURG-GUARD GmbH  
Wormgermühle, 58540 Meinerzhagen, Germany  
Tel.: +49 2358 905 490, Fax: +49 2358 905 499  
BURG-GUARD@burg.biz, www.burg-guard.com



► **Technical specifications:**

Face detect (IVA)	Yes
Audio detect (IVA)	Yes
Alarm management	HTTP, FTP, ONVIF
Schedule	Yes
Edge Recording	Local on desktop, FTP
ANR (automatic network reproduction)	Yes (for records)
Interface	-----
Audio in-/outputs	1x Input: 35 kOhm/2Vpp ; 1x Output: 600 Ohm/2Vpp
Audio codec	G.711a / G711u
Audio sampling rate	8 KHz
Alarm contacts I/O	1 / 1
Switch output contacts	1
Switch input contacts	1
Control interface	No
Relay type (output)	FET (Open Source)
Max. switching voltage	12VDC/0,1A
Max. switching power	1,2W
SD-card slot	Yes, micro SD card up to 128GB
Network	-----
Ethernet connector	RJ-45
Ethernet standards	10Base-TX/100Base-TX
Ethernet speed	10 / 100 Mbit
PoE standard	IEEE802.3at
ePoE / Long-Range-PoE	No
Remote	-----
Max number of users	32
Management software support	Many VMS
Supported browser	Internet Explorer 11
P2P support	Yes (EZCloud)
Cloud service	Yes, EZCloud UNV
Smartphone App	EZView
Push-Notification	Yes, via mobile app.
Security features	HTTPS, SSL, IP Filter
Supported protocols	HTTP,HTTPS,FTP,TCP,UDP, DHCP, SSH,NTP,ONVIF...
Supported software standards	ONVIF, API
ONVIF version/profile	Profile S, Profile G
General	-----
Classification	IP-66
Vandal-proof	No
Installation	Wall and ceiling mount
Camera mounting	Screw mounting
Housing colour	White / black
Housing material	Metal

BURG-GUARD GmbH  
 Wormgermühle, 58540 Meinerzhagen, Germany  
 Tel.: +49 2358 905 490, Fax: +49 2358 905 499  
 BURG-GUARD@burg.biz, www.burg-guard.com



### ► Technical specifications:

Integrated IR-LEDs	Yes
Wavelength LED	850 nm
IR distance (m. ca.)	150m
Smart IR	Yes
DORI max. (Detect-Observe-Recognize-Identify)	1839m - 735m - 368m - 184m
DORI min. (Detect-Observe-Recognize-Identify)	84m - 33m - 17m - 8m
Voltage	12 VDC (+/-10%), PoE
Max. Power consumption (watt)	30
Operating temperature (°C)	-40 to +65
Rel. humidity (%)	Max. 90, non-condensing
Dimensions ØxH (mm)	215 x 344
Weight	3 Kg
Items included in delivery	Mounting accessories, RJ-45 lock

### ► Note:

Uniview Software, z.B. um die Geräte im Netzwerk zu suchen, finden Sie unter Software bzw. Downloads&Software.

### ► Weitere Bilder:



### ► Recommended Accessories

TR-WE45-IN	Uniview PTZ dome wall mounting In-/Outdoor, suitable f. IPC62xx Serie
TR-JB12-IN	Uniview Adapter / junction box suitable for IPC68x Serie, In-/Outdoor
TR-UP08-A-IN	Uniview pole mount suitable for IPC68x series, In-/Outdoor
TR-UC08-A-IN	Uniview Corner mounting suitable for IPC68x Serie, In-/Outdoor

BURG-GUARD GmbH  
 Wormgermühle, 58540 Meinerzhagen, Germany  
 Tel.: +49 2358 905 490, Fax: +49 2358 905 499  
 BURG-GUARD@burg.biz, www.burg-guard.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.