



IPC6415SR-X5UPW-VG

5MP IP Mini Speeddome with 30m IR for indoor use
120dB TrueWDR, 5x opt. zoom, WIFI, Alarm I/O

PRODUCT DESCRIPTION

► Application:

Uniview IP indoor/outdoor camera IPC6415SR-X5UPW-VG with integrated IR-LEDs is the perfect solution for all 24/7 indoor applications. Thanks to its 5MP resolution and the integrated IR-LEDs, the camera delivers detailed and brilliant pictures at all times. The integrated DC 5x autofocus lens with 2,7-13,5mm can be controlled by the webinterface. Specially the integrated speaker and microphone makes it easy to communicate with people around.

► Technical specifications:

Type	IP day/night IR dome camera
Decoding / Video / Lens	>>>>DECODING/VIDEO/LENS<<<<<<
Sensor type	1/2.7" Progressive scan CMOS
Starlight	Yes
Max. Picture resolution (pixel)	5 MP (2592x1944)
Video codec	(U-)H.265,(U-) H.264, MJPEG
Streaming Method	Unicast / Multicast
Max. frame rate (fps)	25/30 frames per second
Bit Rate Control	CBR / VBR
Bit Rate per channel	H.265/H.265: 128-16384Kbps
Number of video streams	3 (individually adjustable)
Lens mount	Intern
Lens type	Built-in motorized lens
Focal length	2,7 - 13,5 mm
Aperture (max)	F1.2
Optical zoom	5x, adjustable

BURG-GUARD GmbH
Wormgermühle, 58540 Meinerzhagen, Germany
Tel.: +49 2358 905 490, Fax: +49 2358 905 499
BURG-GUARD@burg.biz, www.burg-guard.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.



► Recommended Accessories

TR-A01-IN

Uniview plastic Waterproof joint TR-UP06-A-IN,TRJB07-IN,TR-JB07-A-IN

TR-UP06-B-IN

Uniview pole mount adapter suitable for IPC22X- u. IPC24X Serie, Outdoor