



IRN60A8AS00

VIDEOTEC IR-LED illuminator 60°, 850 nm
90/240Vac, distance up to 80m

PRODUCT DESCRIPTION

► Application:

Videotec IR-illuminator of the GEKO series which provides high reliability and excellent product quality. The high efficiency heat sink body ensures maximum LED durability and protection against over-temperatures, whereas the front glass, made of special technopolymer, provides high infrared transmittance. The GEKO illuminators are protected against electrostatic discharges. The GEKO is supplied with a wall-mount bracket that rotates horizontally and vertically.

► Technical specifications:

Type	IR-LED Spotlight
Housing type	Exteriors
Classification	IP-67
Housing material	Aluminium / Plastic
Housing colour	White
IR wave length	850
IR range (m)	up to 80
IR illumination angle (horizontal)	60 °
IR switch contact	Yes
Adjustable Light sensitivity	Yes
Twilight switch	Yes
Voltage	90 - 240 V AC
Max. Power consumption (watt)	30
Operating temperature (°C)	-50 to +60
Dimensions WxHxD (mm)	187x132x176
Weight	2.2 kg

BURG-GUARD GmbH
Wormgermühle, 58540 Meinerzhagen, Germany
Tel.: +49 2358 905 490, Fax: +49 2358 905 499
BURG-GUARD@burg.biz, www.burg-guard.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

► Technical specifications:

Items included in delivery Wall-mount bracket, 2 m multicore cable

► Note:

The range of the built-in IR-LEDs strongly depends on the location and the surroundings. Strongly absorbent surfaces, e.g. dark, rough structures (floor, lawn or asphalt), may lead to a considerable reduction of the maximum range.

► Recommended Accessories

WSFPA Mast clamp adapter for WBJA, WBOVA1, WBOAV2 65-110 mm diameter