



M-500AK-10

10 x Kompakt-Balune für ein Videosignal, Sender
o. Empfänger, 1xBNC-Buchse, 1xJ-45-Buchse

PRODUCT DESCRIPTION

► Application:

A passive, very compact balun for video signal transmission via twisted pair cable. This unit can be used as transmitter or receiver. The max. distance is 600 m depending on cable type. up to 200m when the power should be transferred.

► Technical specifications:

Type	Videobalun, passive
Video input/output	1 x BNC 1 Vpp
Twisted pair input/output	1 x RJ-45 connector
Max. cable length twisted pair (m)	300
Transmission of	Video, Power (24 V AC / 12 V DC)
Adjustable video level	no
Housing material	Plastic
Housing colour	Black
Voltage	None
Operating temperature (°C)	0 to +50
Dimensions WxHxD (mm)	69 x 25 x 20.7 mm
Weight	30 g
Identifier	CE
Specials	Power can be transferred by using an opt. power sup

► Note:

BURG-GUARD GmbH
Wormgermühle, 58540 Meinerzhagen, Germany
Tel.: +49 2358 905 490, Fax: +49 2358 905 499
BURG-GUARD@burg.biz, www.burg-guard.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

Please note: The connector of this balun is not compatible with the SANTEC UTP system technology. To use it together with the SANTEC UTP system technology, please use the video balun VTUD-1.