NS-2080-2000

NUUO NVRsolo 8-Kanal mit 2 TB HDD
Netzwerk Videorekorder, HDMI/VGA

PRODUCT DESCRIPTION

▶ **Application:**

NVRsolo is a Linux-embedded stand-alone system, providing a stable and good quality local display through HDMI and VGA interface. As a network-based surveillance system, NVRsolo processes remote access ability to strengthen its usability. It features two useful functions, one-click setup and ezNUUO. One- click setup saves the time in camera configuration by searching and automatically adding cameras in the system. ezNUUO facilitates the process of establishing Internet access to the NVRsolo system, meaning there is no more router settings for remote (IE 11) and mobile viewing (iPhone, iPad, Android). Being consistent with all the systems in NUUO Mainconsole family, NVRsolo is compatible with NUUO Central Management System and support POS.

▶ **Technical specifications:**

Type	Network videorecorder
Video outputs	HDMI / VGA (max.4 MP IP-cameras)
IP video channels (active)	8
IP Channels (act./ext.)	8/8
Audio inputs	3.5 mm (phone jack)
Audio outputs	3.5 mm (phone jack)
HDD capacity (internal)	2 TB
Max. HDD capacity	12 TB (2 x 6 TB)
External HDD possible	through eSATA
RS-232 interface	Yes, 1x
USB ports	5 x USB 2.0
Ventilation	Fan
Internal RAID	RAID 0,1
DVD-RW	No

BURG GUARD

▶ **Technical specifications:**

Export interface	Network
Control panels (external)	IR remote control/PC mouse/control keyboard
Remote control	IR Remote control
Number of Ethernet ports	2
Ethernet connector	RJ-45
Ethernet speed	10 / 100 / 1000 Mbit
Ethernet standards	10Base-T/100Base-TX/1000Base-TX
Bandwidth Mbps	80
Compression (video)	MPEG-4 / H.264 / MJPEG / MxPEG
Max. frame rate (fps)	120fps @1080p or 240fps @720p
Alarm recording (dig. input)	Yes
Motion recording	Yes
Digital input recording	Yes
Manual recording	Yes
Permanent recording	Yes
Schedule recording	Yes
Live picture	Yes
Mega pixel camera support	Yes
Digital output notification	Yes
CMS notification	Yes
E-mail notification	Yes
Motion detection	Yes
Lost signal detection	Yes
Watermark	Yes
Picture data export	USB / network
Intelligent search	Yes
Intelligent search criteria	motion, missing, foreign, occlusion, signal
Password protection	Yes
Log files	Yes
Supported OS	Windows XP / 7 / 10
Management of IP devices	Yes
DynDNS support	Yes (ezNUUO)
UPNP support	Yes
Preset positions	unlimited
PTZ control	Yes
360° Support	ImmerVision, Vivotek
Remote connections	Yes
Max. remote connections	64
User management	Yes
POS support (cash system)	Yes (optional)
Time syncronisation	NTP protocol
DHCP support	Yes
Access	Browser / Client SW / Mobile App

BURG GUARD

▶ **Technical specifications:**

Supported software for remote access	Remote Viewer
Mobile Client Platform	iPhone, iPad, Android
Firmware upgrade	Network / USB
Housing colour	Black
Max. Power consumption (watt)	Full loading 25 / max. 60
Voltage	12 V DC
Operating temperature (°C)	0 to +40
Storage temperature (°C)	-10 to +50
Rel. humidity (%)	5 - 95
Dimensions WxHxD (mm)	215 x 70.5 x 260
Weight	2.23 kg (w/o HDD)
Identifier	CE, BGV-Kassen
Items included in delivery	IR-Remote Control, CD
Manual language	English

▶ **Recommended Accessories**

HDD-1000HV	HDD for DVR/NVR, 1 TB SATA 24/7 tested
HDD-2000HV	HDD for DVR/NVR, 2 TB SATA 24/7 tested
HDD-4000HV	HDD for DVR/NVR, 4 TB SATA 24/7 tested
HDD-6000HV	HDD for DVR/NVR, 6TB SATA 24/7 tested
NS-SOLO-UP-01	NUUO 1-ch upgrade license for NUUO NVRSolo NS-1040EU
NS-SOLO-UP-04	NUUO 4-channel upgrade license for NUUO NVRSolo NS-1040-EU
SCB-C31APOS	RS-232 to Ethernet converter incl. 1-ch POS license for NUUO systems
SCB-A08	Ethernet I/O Box fits to NUUO systems

BURG GUARD