



NVR301-08LX-P8

SANTEC 4K IP video recorder 8ch
8 Port PoE (without HDD)

PRODUCT DESCRIPTION

► Application:

This network recorder of the Uniview-series has an integrated PoE switch. You will have full flexibility thanks to remote control by using the ez View App or the CMS software. The NVR301-08LX-P8 is also able to support cameras with 4K/Ultra HD resolution (IP cameras with up to 12 mP (ULtra HD)). Camera updates can conveniently be made by using the USB port on the recorder. Newly added cameras are automatically detected when connected to the PoE port. This will reduce installation efforts. The recorder is P2P/Cloud capable (ezCloud and ezView App for iPhone, iPad and Android systems).

► Technical specifications:

Type	Network videorecorder
Decoding / Video / Lens	-----
IP video channels (active)	8
Max. Picture resolution (pixel)	UHD 8 MP (3840x2160)
Video codec	(U-)H.265,(U-) H.264, MJPEG
Streaming Method	Unicast / Multicast
Max. frame rate (fps)	1x 4K@30, 2x 4MP@30, 4x 1080p@30
Bit Rate Control	CBR / VBR
Bit Rate per channel	H.265/H.265: 128-16384Kbps
Number of video streams	2 (1x Main, 1x Sub)
Max. Incoming bandwidth	80Mbps
MAX. Outgoing bandwidth	64Mbps
Playback simultaneously (channels)	4
Features	-----

BURG-GUARD GmbH
Wormgermühle, 58540 Meinerzhagen, Germany
Tel.: +49 2358 905 490, Fax: +49 2358 905 499
BURG-GUARD@burg.biz, www.burg-guard.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

► **Technical specifications:**

Fisheye camera dewarping	No
Automatic delete files	Yes, adjustable days
Camera title	Yes
Privacy zones	Yes
Motion detection	Yes
Tampering Alarm	Yes
Scene change (tampering)	Yes
IVA via ONVIF Motion	No
People counting (IVA+)	Yes
Heatmap (IVA+)	No
Tripwire (IVA)	Yes
Intrusion (IVA)	Yes
Object Apear and disappear (IVA)	No
Fast-Moving (IVA)	No
Crowd Gathering Estimation	No
Loitering detection (IVA)	No
Face detect (IVA)	Yes
Audio detect (IVA)	Yes
Schedule recording	Yes
Alarm recording (dig. input)	Yes, from camera
Motion recording	Yes
Manual recording	Yes
Permanent recording	Yes
Pre-alarm recording	Ja, einstellbar bis zu 60 S.
Post-alarm recording	Yes, adjustable up to 600 s.
Watermark	Yes
Intelligent search criteria	date/time, camra, alarm, motion,IVA
Monitor notification (Popup)	Yes
E-mail notification	Yes
PTZ notification	Yes
Snapshot notification	Yes
Digital output notification	Yes, on-edge (camera)
Password protection	Yes
Log files	Yes
Alarm management	HTTP, FTP, SMTP, ONVIF
Menu languages	German, English and others
Max number of users	128
Schedule	Yes
Edge Recording	Local on desktop
ANR (automatic network reproduction)	Yes (for records)
UPNP support	Yes
Camera update via recorder	Yes

Interface

 BURG-GUARD GmbH
 Wormgermühle, 58540 Meinerzhagen, Germany
 Tel.: +49 2358 905 490, Fax: +49 2358 905 499
 BURG-GUARD@burg.biz, www.burg-guard.com



► **Technical specifications:**

Number of PoE ports	4
PoE status function	Yes, with power information
PoE standard	IEEE802.3at / IEEE802.3af
Power consumption to PoE standard IEEE802.3af	13,5 watt /channel (all ports in use)
Power consumption to PoE standard IEEE802.3at	30 watt single port
Max. PoE power consumption	54W
Number of Ethernet ports	5
ePoE / Long-Range-PoE	Yes, up to 300m (certain camera models)
Ethernet connector	RJ-45
Ethernet standards	10Base-TX/100Base-TX
Ethernet speed	10 / 100 Mbit
Monitor outputs	HDMI (max. 4K), VGA (max. 2MP)
Spot monitor outputs	No, simultaneous output HDMI/VGA
Max. number of HDDs (internal)	1 x SATA
Max. HDD capacity	10 TB
Internal RAID	No
DVD-RW	No
USB interface	1 xUSB 2.0, 1 x USB 3.0
USB ports	2 x Back side
RS-232 interface	No
RS-485 interface	No
Control panels (external)	IR remote control / PC mouse
Export interface	USB/network
Audio in-/outputs	Output: 1x RCA, Input: 1x RCA
Switch input contacts	No
Switch output contacts	No
SD-card slot	No
eSATA	No
Remote	-----
Management software support	Many VMS
Supported browser	Internet Explorer 11
P2P support	Yes (EZCloud)
Cloud service	Yes, EZCloud UNV
Smartphone App	EZView
Push-Notification	Yes, via mobile app.
Security features	HTTPS, SSL, IP Filter
Supported protocols	P2P, UPnP, NTP, DHCP, PPPoE,SSL,TLS,SNMP,HTTPS
Supported software standards	ONVIF, API
ONVIF version/profile	Profile S, Profile G, C, Q, A,T
Supported software for remote access	Web-Plug-In, APP (iPhone, Android)
General	-----

BURG-GUARD GmbH
 Wormgermühle, 58540 Meinerzhagen, Germany
 Tel.: +49 2358 905 490, Fax: +49 2358 905 499
 BURG-GUARD@burg.biz, www.burg-guard.com



► Technical specifications:

Housing colour	White
Housing material	Aluminium / Plastic
Fan	Yes
Voltage	52Vdc using external power supply 230VAC/3A
Max. Power consumption (watt)	8W (without HDD)
Operating temperature (°C)	-10 to +55
Rel. humidity (%)	Max. 90, non-condensing
Dimensions WxDxH (mm)	270 x 205 x 57
Weight	0,7 Kg

► Note:

Uniview Software, z.B. um die Geräte im Netzwerk zu suchen, finden Sie unter Software bzw. Downloads&Software.

► Weitere Bilder:



► Recommended Accessories

HDD-1000HV	HDD for DVR/NVR, 1 TB SATA 24/7 tested
HDD-2000HV	HDD for DVR/NVR, 2 TB SATA 24/7 tested
HDD-4000HV	HDD for DVR/NVR, 4 TB SATA 24/7 tested
HDD-6000HV	HDD for DVR/NVR, 6TB SATA 24/7 tested