



### SANSWITCH-10430

4-Port ePoE Switch  
For transmission over 800m

## PRODUCT DESCRIPTION

### ► Application:

Sanswitch-10430 is a 4-Port ePoE switch, which is able to realize PoE transmission over 800 meters Ethernet cable at the speed of 10Mbps, or 300 meters at the speed of 100Mbps.

### ► Technical specifications:

Type	ePoE Switch
Number of Ethernet ports	5 + 1 SFP
Ethernet standards	10Base-T/100Base-TX/1000Base-TX
Ethernet connector	RJ-45
Power over Ethernet (PoE)	Yes, Port 1-3<30W, Port 4<60W
Max. PoE Output Voltage (port)	Total <96W
PoE standard	IEEE802.3at / IEEE802.3af / ePoE
Communication standards	IEEE802.3, IEEE802.3u, IEEE802.3ab/z, IEEE802.3X
Flow control	Yes
Cable type	CAT5E, CAT6, CAT7
Switch capacity (Gbit/s)	6,8
MAC address memory (KB)	8K
MAC address update	auto
RS-232 interface	No
Weight	480g
Voltage	100 - 240 V AC
Operating temperature (°C)	0 to +40
Rel. humidity (%)	10 - 90, non-condensing
Rack mount (U)	1

BURG-GUARD GmbH  
Wormgermühle, 58540 Meinerzhagen, Germany  
Tel.: +49 2358 905 490, Fax: +49 2358 905 499  
BURG-GUARD@burg.biz, www.burg-guard.com



### ► Technical specifications:

Fan	No
Max. Power consumption (watt)	150
Dimensions WxHxD (mm)	150 x 30 x 100
Identifier	CE, FCC
Items included in delivery	Power adapter
Specials	ePoE transmission up to 800m

### ► Recommended Accessories

SAN-GBIC-LX-10	Fiber Optics Adaptor, Singlemode LC/LC connector, up to 10 km
SAN-GBIC-SX	Fiber Optics Connector, multimode LC/LC connector, up to 500 m
NWK-P0.55ES2	0,5m Patchcabel CAT5e, SF/UTP
NWK-P3.05ES2	3m Patchkabel CAT5e, SF/UTP